INDUSTRIAL COMPONENT DATA

YD4037N BTCINO LW-PULS DOUBLE LOCK 10A 1M DK

Brand: BTICINO | Manufacturer Part Number: YD4037N

Manufacturer	BTICINO
MPN / Reference	YD4037N
Catalog number	YD4037N
Category	Venetian blind switch/-push button
Minimum order	10 Pcs
Document ID	EO-3B9443EDC9
Generated	2026-07-29

Product Overview

LW-PULS DOUBLE LOCK 10A 1M DK
Double push button for Light Now blinds - 10A - 250V~ - interlocked push button - 1 module - dark
Double push button for Light Now-10A-250V blinds~-interblocked-1 module-dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	BTICINO > MATIX MECHANISMS

Additional Product Information

Shutter mechanisms - Double dark push button with mechanical lock - 10 A - 250 Vac - One press to activate the maneuver and when released it stops - To be combined with support and decorative plate - 1 module.For Venetian blinds Yes
For blinds Yes
For awnings No
Type of mounting Module for system interruption program, Recessed mounted (plaster)
Model 1-pole push button
Number of poles 1
Type of operation Seesaw
With electric lock No
With mechanical latch No
Mechanically Driven Yes
Electronically operated No
Material Plastic
Material quality Thermoplastic

Halogen-free Yes
Surface treatment Varnishing
Surface Finish Mate
Attachment Type Lock in position
Connection Method Screw-on terminal
Colour Black
RAL number (similar) 9011
Transparent Yes
Label Space/Print Area No
Suitable for protection grade (IP) IP20
Nominal current 10 A
Nominal Voltage 250 V
Number of buttons 1
Number of modules (in case of modular design) 1
Device width 22.5 mm
Device height 45 mm
Device Depth 36.5 mm
Installation Depth 28.5 mm
Min. depth of the recessed box 38.5 mm
Compatible with Apple HomeKit No
Compatible with Google Assistant No
Compatible with Amazon Alexa No
Compatible IFTTT No
Impact resistance IK04
Operating Temperature -5-35 °C
Storage temperature -10-70 °C
Type of voltage AC
frequency 50-60 Hz
Lighting Type Not included
Display of markings on the connection terminals No
Antibacterial treatment No
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Cor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / YD4037N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.