

## INDUSTRIAL COMPONENT DATA

## YD4192C BTCINO LW-BASE USB C 3A 20W PD 1M DK

Brand: BTICINO | Manufacturer Part Number: YD4192C



|                 |                  |
|-----------------|------------------|
| Manufacturer    | BTICINO          |
| MPN / Reference | YD4192C          |
| Catalog number  | YD4192C          |
| Category        | USB power supply |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-FF6294BE26    |
| Generated       | 2026-08-02       |

## Product Overview

LW-BASE USB C 3A 20W PD 1M DK

Single USB Charger Base Light Now - Type C - 1 module - Dark

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path BTICINO &gt; MATIX MECHANISMS

## Additional Product Information

Universal USB chargers - Type C - 3A - 5Vdc - 20W - Compliant with IEC62368-1 standard - Allow charging of mobile phones, tablets, smartphones, MP3, MP4 - Standby consumption 0.05 W - Class II TBTS - Complies with the EEC directive on the harmonization of the standard for charging portable terminals and the reduction of mobile chargers - To be combined with stand and decorative plate - 1 module.

Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-12 V

Power consumption 0.048 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black

RAL number 9011

Device width 22.5 mm  
Device height 45 mm  
Device Depth 41 mm  
Min. depth of the recessed box 43 mm  
Suitable for protection grade (IP) IP40  
Impact resistance IK04  
Antibacterial treatment No  
Wireless No  
Installation Depth 33 mm  
Operating Temperature -5-35 °C  
Storage temperature -10-70 °C  
Type of voltage AC  
Power Delivery Yes  
USB Power Output 20  
Nominal current 0.5-0.5 A  
Neutral Mandatory Yes  
Display of markings on the connection terminals Yes  
Compliant with commissioning tests (1000 V) No  
Halogen-free Yes  
Number of terminals 2  
Terminal capacity 1.5-2.5 mm<sup>2</sup>  
Connection Cable Type Flexible or rigid  
Core cross-section 1.5-2.5 mm<sup>2</sup>  
ETIM for YD4192C Domestic wiring accessories and controls (EC002949)  
Feature Name  
Feature Value  
Model (EF000010)  
Other  
Mounting method (EF000003)  
Flush mounted  
Suitable for deg...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / YD4192C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.