

INDUSTRIAL COMPONENT DATA

YD4294C BTCINO LW-BASE USB C 45W PD 2M DK

Brand: BTCINO | Manufacturer Part Number: YD4294C



Manufacturer	BTCINO
MPN / Reference	YD4294C
Catalog number	YD4294C
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-A9B2CAD914
Generated	2026-08-02

Product Overview

LW-BASE USB C 45W PD 2M DK

Single USB Charger Base Light Now - Type C Power Delivery - 1 module - Dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTCINO > MATIX MECHANISMS**

Additional Product Information

Universal USB Chargers - Type C Power Delivery - 3A - 5Vdc - 45W - Allow the charging of mobile phones, tablets, smartphones, MP3, MP4, laptops - Standby consumption 0.1 W - Class II TBTS - Complies with the EEC directive on the harmonization of the standard of charging of portable terminals and the reduction of mobile chargers - To be combined with stand and decorative plate - 1 module. Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 220-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-20 V

Power consumption 0.074 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black

RAL number 9011

Device width 45 mm
Device height 45 mm
Device Depth 41 mm
Min. depth of the recessed box 43 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 33 mm
Operating Temperature -5-35 °C
Storage temperature -10-70 °C
Type of voltage AC
Power Delivery Yes
USB Power Output 45
Nominal current 0.8-0.8 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for YD4294C Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounted
Suitable for degree of pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / YD4294C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.