

INDUSTRIAL COMPONENT DATA

IA18ESN08UCM1 CARLO GAVAZZI CONNECTION M12 WIRE 2-wire MATERIAL Metal SYSTEM Proximity Sensor Others HOUSING..

Brand: CARLO GAVAZZI | Manufacturer Part Number: IA18ESN08UCM1



Manufacturer	CARLO GAVAZZI
MPN / Reference	IA18ESN08UCM1
Catalog number	10000
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-D1D9AABEF9
Generated	2026-08-05

Product Overview

CONNECTION M12 WIRE 2-wire MATERIAL Metal SYSTEM Proximity Sensor Others HOUSING M18 x 63 mm

MATERIAL Stainless steel SENSING RANGE 8 mm

Inductive namur M18, M12 connector, non-flush mounting, sensing distance 8 mm, short box type

Inductive proximity sensor, M18 Stainless steel, M12 plug, Sn 8mm, Non- Flush mount, Short body, Namur NC, Supply voltage 7-9Vdc, Max output current 9,35 mA, Max switching frequency 200Hz, Operating temperature -25C - +70C, IP67.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Inductive and Loop Detector

Additional Product Information

Specifications

Rated operating distance8 mmInstallation typeFlushDiameterM18Output typeNamurOutput functionNormally Closed

(NC)Connection typePlug-in connectionHousing typeCylindrical, threaded barrelHousing materialMetalRated power supply7 V ... 9 V

ETIM for IA18ESN08UCM1 Sensors (EC002714)

Feature Name

Feature Value

Length of sensor (EF007334)

30 mm

Diameter sensor (EF007111)
18 mm
Mechanical mounting condition for sensor (EF004041)
Concise
Switching distance (EF003647)
8 mm
Type of switch function (EF003963)
Breaker contact
Type of switching output (EF003962)
NAMUR
Type of electric connection (EF003961)
Plug-in connection
Number of protected semiconductor outputs (EF003951)
1
Type of actuation (EF006949)
Metallic Target
Construction type housing (EF004008)
Cylinder, screw-thread
Max. output current at protected output (EF004035)
9.35 mA
Supply voltage (EF004127)
7 V
Rated control supply voltage DC (EF003980)
7 V
Voltage type (EF000187)
DC
Switching frequency (EF003587)
200 Hz
Housing material (EF001596)
Metal

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / IA18ESN08UCM1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.