

INDUSTRIAL COMPONENT DATA

ICB18L50N14A2IO CARLO GAVAZZI Inductive Sensor, 3 wire DC, Metric 18, Housing lantón plated, IO-Link Communi..

Brand: CARLO GAVAZZI | Manufacturer Part Number: ICB18L50N14A2IO



Manufacturer	CARLO GAVAZZI
MPN / Reference	ICB18L50N14A2IO
Catalog number	10000
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-52AB0B6DC6
Generated	2026-08-06

Product Overview

Inductive Sensor, 3 wire DC, Metric 18, Housing lantón plated, IO-Link Communication

Inductive proximity sensor, M18 Nickel-Plated Brass, 2m cable, Sn 14mm, Non-Flush mount, Long body, NPN/PNP/Push-pull, NO/NC, Supply voltage 10-36Vdc, Max output current 200 mA, Max switching frequency 1.5 kHz, Operating temp. -25C - +70C, IP67, IO-Link

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Inductive and Loop Detector

Additional Product Information

Specifications

Rated operating distance14 mmInstallation typeNon-flushDiameterM18Output typePNP/NPNOutput functionProgrammable/configurableConnection typeCableHousing typeCylindrical, threaded barrelHousing materialMetalRated power supply10 V ... 36 V

ETIM for ICB18L50N14A2IO Sensors (EC002714)

Feature Name

Feature Value

Length of sensor (EF007334)

62 mm

Diameter sensor (EF007111)

18 mm

Mechanical mounting condition for sensor (EF004041)

Not flat

Switching distance (EF003647)

14 mm

Suitable for safety functions (EF001597)

No

Type of switch function (EF003963)

Programmable/configurable

Type of switching output (EF003962)

PNP/NPN

Type of electric connection (EF003961)

Cable

Number of semiconductor outputs with signalling function (EF003945)

1

Number of protected semiconductor outputs (EF003951)

1

Type of actuation (EF006949)

Metallic Target

Type of interface (EF006977)

Other

Type of interface for safety communication (EF003956)

None

Construction type housing (EF004008)

Cylinder, screw-thread

Coating housing (EF001601)

Nickel-plated

Cascadable (EF000507)

No

Max. output current at protected output (EF004035)

200 mA

Supply voltage (EF004127)

10 V

Rated control supply voltage DC (EF003980)

10 V

Voltage type (EF000187)

DC

Switching frequency (EF003587)

1500 Hz

Housing material (EF001596)

Metal

Compression-resistant (EF007106)

No

Interference resistance to magnetic fields (EF008275)

Immune against magnetic DC- and AC-field

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / ICB18L50N14A2IO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.