

INDUSTRIAL COMPONENT DATA

**DAA51CM24 CARLO GAVAZZI INPUT RANGE 0,1 s 100 h
MOUNTING DIN-rail SIZE 17,5 mm POWER SUPPLY RANGE
24÷240VAC ..**

Brand: CARLO GAVAZZI | Manufacturer Part Number: DAA51CM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	DAA51CM24
Catalog number	24240
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-6C840637EE
Generated	2026-08-04

Product Overview

INPUT RANGE 0,1 s - 100 h MOUNTING DIN-rail SIZE 17,5 mm POWER SUPPLY RANGE 24÷240VAC and 24VDC
SOCKET N/A

Timer, connection delay, DIN rail mounting, Mini D box, 17.5 mm., SPDT 8A output

Delay on operate timer, time range 0.1 s - 100 h, automatic start, supply voltage 24 V DC and 24-240 V AC, SPDT relay output, 17.5 mm DIN-rail housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Timers
--------------	-----------------------------------

Additional Product Information

Specifications

MountingMini DIN-railOutput1 relayDelay time rangeUp to 10s; Up to 60s; Up to 600s;

Multi-rangeTerminalsScrewApprovals, marks, declarationfor Europe; for North America; for Australia

ETIM for DAA51CM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Function delay-on energization (EF003374)

Yes

Function delay on de-energization (EF003401)

No

Function floating contact on energization (EF003378)

No

Function floating contact on de-energization (EF003402)

No

Function star-delta (EF003380)

No

Function pulse shaping (EF003403)

No

Function flashing, starting with pause, fixed time (EF003363)

No

Function flashing, starting with pulse, fixed time (EF003364)

No

Clock function, starting with pause, variable (EF003365)

No

Clock function, starting with pulse, variable (EF003366)

No

Remote operation possible (EF003361)

No

Suitable as remote control (EF003362)

No

Pluggable on auxiliary contact block (EF006952)

No

Rated control supply voltage AC 50 Hz (EF003978)

20.4 V

Rated control supply voltage AC 60 Hz (EF003979)

20.4 V

Rated control supply voltage DC (EF003980)

20.4 V

Voltage type for actuating (EF008242)

AC/DC

Time range (EF003384)

0.1 s

Number of outputs, delayed, change-over contact (EF006840)

1

Outputs, reversible delayed/undelayed (EF006988)

No

With semiconductor output (EF003373)

No

Width (EF000008)

17.5 mm

Height (EF000040)

81 mm

Depth (EF000049)

67.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DAA51CM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.