

INDUSTRIAL COMPONENT DATA

SPD242401 CARLO GAVAZZI MODEL Din Rail AC INPUT VOLTAGE 93 264V OUTPUT POWER 240W PARALLEL CONNECTION yes IN..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPD242401



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPD242401
Catalog number	242401
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-F7E06993F1
Generated	2026-08-04

Product Overview

MODEL Din Rail AC INPUT VOLTAGE 93 - 264V OUTPUT POWER 240W PARALLEL CONNECTION yes INPUT TYPE Single phase or DC OUTPUT VOLTAGE 24Vdc PFC yes DC INPUT VOLTAGE 210 - 370V TERMINAL TYPE Screw terminal OUTPUT RDY Relay SPST Others DESCRIPTION 240W, Screw terminals, PFC, Parallel function, RDY out Switching power supply, output 24Vdc, output current 10 A, output power 240 W Switching Power Supply, AC/DC, 240W, 24V, Screw Terminals, IP20, DIN-Rail Mounting, Over-load, Over-voltage and Short-circuit Protections, 83.5x124.5x123,6mm metallic housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Power supplies

Additional Product Information

Specifications

Rated output voltage DC24 VPower output240 WMax. output current DC10 ATerminal typeScrew connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width83.5 mmHeight124.5 mmDepth123.6 mm ETIM for SPD242401 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

23.76 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

10 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

10 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

115 V

Rated supply voltage AC 60 Hz (EF007077)

115 V

Rated supply voltage DC (EF007078)

210 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

35 VA

Power output (EF003034)

240 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No
Modular version (EF001126)
No
Width in number of modular spacings (EF002950)
0
Built-in width (EF000846)
83.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPD242401 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.