

INDUSTRIAL COMPONENT DATA

PD30CNB25PAPS CARLO GAVAZZI System: DiffuseÂ reflective BGS, Housing: rectangular, Sensing range: 200 ... 40..

Brand: CARLO GAVAZZI | Manufacturer Part Number: PD30CNB25PAPS



Manufacturer	CARLO GAVAZZI
MPN / Reference	PD30CNB25PAPS
Catalog number	10000
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-1A37756A69
Generated	2026-07-28

Product Overview

System: DiffuseÂ reflective BGS, Housing: rectangular, Sensing range: 200 ... 400 mm, Connection: Cable, Output: DC PNP, Material: Plastic, Sensing range: 250 mm, Housing: 30 x 20 x 10,8 mm, Material: ABS , Additional: PointSpot Photoelectric sensor background suppression, miniature - PointSpot, with a knob in the rear
Diffuse-reflective Photoelectric Sensor with Adjustable Background Suppression, Range: 0-200mm, Polarity free red light 625nm, Power Supply 10-30VDC, PNP Output, N.O. and N.C., light and dark switching, Cable connection, 10x30x20mm housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Photoelectric

Additional Product Information

Specifications

Rated operating distance250 mmOutput typePNPOutput functionComplementary (NO+NC)Connection typeCableHousing typeRectangularHousing materialPlasticEmitted lightPolarity free red lightSensing modeLight-/dark switchingDegree of protectionIP67Rated power supply10 V ... 30 V

ETIM for PD30CNB25PAPS Sensors (EC002719)

Feature Name

Feature Value

Adjustment range (EF002300)

25 mm

Triangulation (EF008296)

Background fade-out

Pre failure notice (EF004129)

No

With time function (EF003582)

No

Rated switching distance (EF008289)

250 mm

Max. switching distance (EF007367)

250 mm

Max. output current (EF001315)

100 mA

With reflector (EF007448)

No

Analogue output 0 V ... 10 V (EF006807)

No

Analogue output 0 mA ... 20 mA (EF006808)

No

Analogue output 4 mA ... 20 mA (EF006810)

No

Analogue output -10 V ... +10 V (EF006809)

No

With other analogue output (EF007485)

No

Setting procedure (EF003994)

Manual adjustment

With communication interface analogue (EF007305)

No

With communication interface AS-Interface (EF007306)

No

With communication interface CANOpen (EF007307)

No

With communication interface DeviceNet (EF007308)

No

With communication interface Ethernet (EF007309)

No

With communication interface INTERBUS (EF007310)

No

With communication interface PROFIBUS (EF007311)

No

With communication interface RS-232 (EF007312)

No

With communication interface RS-422 (EF007313)

No

With communication interface RS-485 (EF007314)

No

With communication interface SSD (EF007315)

No

With communicat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PD30CNB25PAPS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.