

## INDUSTRIAL COMPONENT DATA

# DUB02CT23 CARLO GAVAZZI POWER SUPPLY RANGE 24/115/230 VAC MONITORING FUNCTION Over and under voltage MOUTING..

Brand: CARLO GAVAZZI | Manufacturer Part Number: DUB02CT23



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | CARLO GAVAZZI            |
| MPN / Reference | DUB02CT23                |
| Catalog number  | 10000                    |
| Category        | Voltage monitoring relay |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-5AA1CF1673            |
| Generated       | 2026-08-05               |

## Product Overview

POWER SUPPLY RANGE 24/115/230 VAC MONITORING FUNCTION Over and under voltage MOUTING DIN-rail INPUT RANGE 24/115/230 VAC DELAY 1, adjustable  
Single-phase control relay of max./min AC voltage (TRMS), DIN rail mounting  
1-phase AC over and undervoltage monitoring relay, nominal range 24/115/230 V AC, SPDT relay output, 22.5 mm DIN-rail housing

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path CARLO GAVAZZI > Controls > Monitoring Relays and Measurement Current Transformers

## Additional Product Information

## Specifications

Supply VoltageSelf-poweredMountingIndustrial DIN-rail1-phase ac/dc voltage functionOver and undervoltageMonitored voltageMonitoring own power supply1-phase voltage range24-240 Vac/dcOutput1 relayTime delayDelay on alarm  
ETIM for DUB02CT23 Relays (EC001438)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

With detachable clamps (EF003340)

No  
Single-phase under voltage possible (EF003390)  
No  
Single-phase over voltage possible (EF003392)  
No  
Three-phase over voltage possible (EF003393)  
Yes  
Single-phase hysteresis possible (EF003394)  
Yes  
Voltage measuring range 2 (EF006135)  
0 V  
Type of voltage measuring range (EF003399)  
AC  
Response value voltage (EF008193)  
19.2 V  
Min. adjustable delay-on energization time (EF008190)  
0.1 s  
Max. permitted delay-on energization time (EF008189)  
30 s  
Min. adjustable off-delay time (EF008192)  
0.1 s  
Max. permitted off-delay time (EF008191)  
30 s  
Number of contacts as change-over contact (EF008257)  
1  
Width (EF000008)  
22.5 mm  
Height (EF000040)  
80 mm  
Depth (EF000049)  
99.5 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DUB02CT23 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.