

INDUSTRIAL COMPONENT DATA

PS21H-MO11HC-T00 CARLO GAVAZZI Ps 30Mm Tt 1No+1Nc Overlap Slow(+) Head Hc

Brand: CARLO GAVAZZI | Manufacturer Part Number: PS21H-MO11HC-T00



Manufacturer	CARLO GAVAZZI
MPN / Reference	PS21H-MO11HC-T00
Catalog number	10000
Category	Hinge switch
Minimum order	1 Pcs
Document ID	EO-F12012354D
Generated	2026-08-06

Product Overview

Ps 30Mm Tt 1No+1Nc Overlap Slow(+) Head Hc

Final degree

Electromechanical safety limit switch; adjustable rotative lever; 30x30mm plastic housing; 1NO+1NC slow-action in overlap contacts; M20 cable gland; IP65; -25 - +70C operating temperature

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Light Curtains and Safety Light Curtains
--------------	--

Additional Product Information

Specifications

Control elementFull shaftSwitching functionSlow-action switchNumber of contacts as normally open contact1Normally open contactsNumber of contacts as normally closed contact1Normally closed contactsHousing materialPlasticDegree of protectionIP65

ETIM for PS21H-MO11HC-T00 Sensors (EC002591)

Feature Name

Feature Value

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Type of control element (EF006976)

Full shaft
Forced opening (EF006694)
No
Number of safety auxiliary contacts (EF006940)
0
Number of contacts as normally closed contact (EF008255)
1
Number of contacts as normally open contact (EF008256)
1
Number of contacts as change-over contact (EF008257)
0
Type of switching contact (EF003591)
Slow-action switch
Width sensor (EF007094)
30.3 mm
Height of sensor (EF007283)
39 mm
Length of sensor (EF007334)
169.5 mm
Rated operation current I_e at AC-15, 24 V (EF007084)
10 A
Rated operation current I_e at AC-15, 125 V (EF007082)
5.5 A
Rated operation current I_e at AC-15, 230 V (EF001385)
3.1 A
Rated operation current I_e at DC-13, 24 V (EF007087)
2.8 A
Rated operation current I_e at DC-13, 125 V (EF007085)
0.6 A
Rated operation current I_e at DC-13, 230 V (EF001386)
0.27 A
Construction type housing (EF004008)
Cuboid
Housing material (EF001596)
Plastic
Coating housing (EF001601)
Other
Type of electric connection (EF003961)
Cable entry metrical
Explosion safety category for gas (EF003997)
None
Explosion safety category for dust (EF003998)
None...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PS21H-MO11HC-T00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.