

INDUSTRIAL COMPONENT DATA

PS42S-AS1105-T00 CARLO GAVAZZI Ps 50Mm Tt 1No+1Nc Snap(+) Head 05

Brand: CARLO GAVAZZI | Manufacturer Part Number: PS42S-AS1105-T00



Manufacturer	CARLO GAVAZZI
MPN / Reference	PS42S-AS1105-T00
Catalog number	10000
Category	Position switch with separate actuator
Minimum order	1 Pcs
Document ID	EO-E7CDDC39A6
Generated	2026-08-06

Product Overview

Ps 50Mm Tt 1No+1Nc Snap(+) Head 05

Final degree

Safety electromechanical limit switch for key actuator; 90deg adjustable key plastic head; 1NO+1NC snap-on contacts; 50x33mm plastic housing; M16 cable gland; IP65; -25C - +70C operating temperature

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Light Curtains and Safety Light Curtains

Additional Product Information

Specifications

Switching functionQuick-action switchNormally open contacts1Normally open contactsNormally closed contacts1Normally closed contactsDegree of protectionIP65Housing materialPlastic housingOperating temperature-25 °C ... 70 °C

ETIM for PS42S-AS1105-T00 Sensors (EC002592)

Feature Name

Feature Value

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Width sensor (EF007094)

50 mm

Height of sensor (EF007283)

33 mm

Length of sensor (EF007334)

83 mm

Forced opening (EF006694)

Yes

Number of safety auxiliary contacts (EF006940)

2

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as normally open contact (EF008256)

1

Number of contacts as change-over contact (EF008257)

0

Type of switching contact (EF003591)

Quick-break switch

Rated operation current I_e at AC-15, 24 V (EF007084)

10 A

Rated operation current I_e at AC-15, 125 V (EF007082)

5.5 A

Rated operation current I_e at AC-15, 230 V (EF001385)

3.1 A

Rated operation current I_e at DC-13, 24 V (EF007087)

2.8 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0.6 A

Rated operation current I_e at DC-13, 230 V (EF001386)

0.27 A

Construction type housing (EF004008)

Cuboid

Housing material (EF001596)

Plastic

Coating housing (EF001601)

Other

Type of interface (EF006977)

None

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Cable entry metrical

Explosion safety category for gas (EF003997)

None

Explosion safety category fo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PS42S-AS1105-T00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.