


INDUSTRIAL COMPONENT DATA

RMIA21012AC CARLO GAVAZZI Emrelay Solder 2Dpdt 10A Coil 12Vac

Brand: CARLO GAVAZZI | Manufacturer Part Number: RMIA21012AC



Manufacturer	CARLO GAVAZZI
MPN / Reference	RMIA21012AC
Catalog number	21012
Category	Switching relay
Minimum order	20 Pcs
Document ID	EO-B26692E820
Generated	2026-08-06

Product Overview

Emrelay Solder 2Dpdt 10A Coil 12Vac

Industrial Electromechanical Relays series, 10A 250VAC/30VDC, 8 poles, DPDT (2 Change Over contacts), Coil voltage 12VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Industrials Relays and sockets

Additional Product Information

Specifications

Rated control supply voltage Us at AC 50HZ12 V ... 12 VRated control supply voltage Us at DC0 V ... 0 VNominal current10

ANumber of contacts as normally closed contact2Number of contacts as normally open contact2Number of contacts as change-over contact2Type of electric connectionPlug-in connection; Plug-in connectionWith LED indicationYesMaterial contactBeryllium copper

ETIM for RMIA21012AC Relays (EC001437)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

With detachable clamps (EF003340)

No

Nominal current (EF000001)

10 A
Rated control supply voltage AC 50 Hz (EF003978)
12 V
Rated control supply voltage AC 60 Hz (EF003979)
12 V
Rated control supply voltage DC (EF003980)
0 V
Voltage type for actuating (EF008242)
AC
Drive, polarization (EF003355)
Polarity free
Drive, switching attitude (EF003356)
Mono stable
Number of contacts as normally closed contact (EF008255)
2
Number of contacts as normally open contact (EF008256)
2
Number of contacts as change-over contact (EF008257)
2
With forced-guided contacts (EF003357)
No
Type of switch contact (EF003358)
Double contact
Complete with socket (EF003359)
No
With LED indication (EF005950)
Yes
Material of contact surface (EF004020)
Silver
Material of contact insert (EF008521)
Thermoplastic
Material contact (EF007544)
Beryllium copper
Degree of protection (IP) (EF005474)
IP40
Width (EF000008)
28 mm
Height (EF000040)
21.5 mm
Depth (EF000049)
36 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RMIA21012AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.