

INDUSTRIAL COMPONENT DATA

RMIA4524DC CARLO GAVAZZI Emrelay Solder 4Pdt 5A Coil 24Vdc

Brand: CARLO GAVAZZI | Manufacturer Part Number: RMIA4524DC



Manufacturer	CARLO GAVAZZI
MPN / Reference	RMIA4524DC
Catalog number	10000
Category	Switching relay
Minimum order	20 Pcs
Document ID	EO-50EAA736B4
Generated	2026-08-06

Product Overview

Emrelay Solder 4Pdt 5A Coil 24Vdc

Industrial Electromechanical Relays series, 5A 250VAC/30VDC, 14 poles, 4PDT (4 Change Over contacts), Coil voltage 24VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **CARLO GAVAZZI > Switches > Industrials Relays and sockets**

Additional Product Information

Specifications

Rated control supply voltage Us at AC 50HZ0 V ... 0 VRated control supply voltage Us at DC24 V ... 24 VNominal current5

ANumber of contacts as normally closed contact4Number of contacts as normally open contact4Number of contacts as

change-over contact4Type of electric connectionPlug-in connection; Plug-in connectionWith LED indicationYesMaterial

contactBeryllium copper

ETIM for RMIA4524DC Relays (EC001437)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

With detachable clamps (EF003340)

No

Nominal current (EF000001)

5 A
Rated control supply voltage AC 50 Hz (EF003978)
0 V
Rated control supply voltage AC 60 Hz (EF003979)
0 V
Rated control supply voltage DC (EF003980)
24 V
Voltage type for actuating (EF008242)
DC
Drive, polarization (EF003355)
Polarity free
Drive, switching attitude (EF003356)
Mono stable
Number of contacts as normally closed contact (EF008255)
4
Number of contacts as normally open contact (EF008256)
4
Number of contacts as change-over contact (EF008257)
4
With forced-guided contacts (EF003357)
No
Type of switch contact (EF003358)
Other
Complete with socket (EF003359)
No
With LED indication (EF005950)
Yes
Material of contact surface (EF004020)
Silver
Material of contact insert (EF008521)
Thermoplastic
Material contact (EF007544)
Beryllium copper
Degree of protection (IP) (EF005474)
IP40
Width (EF000008)
42.4 mm
Height (EF000040)
28 mm
Depth (EF000049)
21.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RMIA4524DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.