

INDUSTRIAL COMPONENT DATA

RSBD6070GGV61HP CARLO GAVAZZI System: Soft Starter, Load: Phase 3, Housing width: 45mm to 90mm, Motor rating..

Brand: CARLO GAVAZZI | Manufacturer Part Number: RSBD6070GGV61HP



Manufacturer	CARLO GAVAZZI
MPN / Reference	RSBD6070GGV61HP
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-7D95AB52EB
Generated	2026-08-05

Product Overview

System: Soft Starter, Load: Phase 3, Housing width: >45mm to 90mm, Motor rating: >50kW to 80kW, Operational voltage: Up to 700VAC, Load current: >50A to 75A, Controlled phases: 2-Phase, Max number of stats per hour: >10 to 20, Load (result): Soft Starting of 3-Phase scroll compressors, Load current: 70A AC, Max motor rating: 55 kW , Operational voltage: 187 - 660V ACrms, Dimensions: 75 x 150 x 170 mm, Controlled phases: 2-Phase, Max number of stats per hour: 12
Soft start three-phase scroll compressors 70 A; 2 controlled phases; High pressure start; 75 mm
3 phase soft starter for scroll compressors, Operating voltage (Ue): 220 - 600 Vac , Rated current (Ie): 70 Aac, Control voltage (Uc): 100 - 240 Vac , DIN rail/Panel mount, Supply voltage (Us): 100 - 240 Vac , 2-phase control

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Frequency Drives and Limit

Additional Product Information

Specifications

Rated operation current Ie at 40 °C Tu70 ARated operating voltage Ue187 V ... 660 VRated power three-phase motor, inline, at 230 V20 kWRated power three-phase motor, inline, at 400 V37 kWRated control supply voltage Us at AC 50HZ85 V ... 264 VRated control supply voltage Us at DC0 V ... 0 VInternal bypassYesProduct Width75 mmProduct Height170 mmProduct Depth150 mm

ETIM for RSBD6070GGV61HP Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Rated operation current Ie at 40 °C Tu (EF007039)

70 A
Rated operating voltage Ue (EF002418)
187 V
Rated power three-phase motor, inline, at 230 V (EF007053)
20 kW
Rated power three-phase motor, inline, at 400 V (EF007054)
37 kW
Function (EF000030)
Single direction
Internal bypass (EF009214)
Yes
With display (EF000458)
No
Torque control (EF009215)
No
Rated surrounding temperature without derating (EF007074)
40 °C
Rated control supply voltage AC 50 Hz (EF003978)
85 V
Rated control supply voltage AC 60 Hz (EF003979)
85 V
Rated control supply voltage DC (EF003980)
0 V
Voltage type for actuating (EF008242)
AC
Integrated motor overload protection (EF007297)
No
Release class (EF006668)
Other
Degree of protection (IP) (EF005474)
IP20
Degree of protection (NEMA) (EF011959)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RSBD6070GGV61HP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.