

## INDUSTRIAL COMPONENT DATA

# RSBD6095FFV61HP CARLO GAVAZZI System: Soft Starter, Load: Phase 3, Housing width: 45mm to 90mm, Motor rating..

Brand: CARLO GAVAZZI | Manufacturer Part Number: RSBD6095FFV61HP



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | CARLO GAVAZZI   |
| MPN / Reference | RSBD6095FFV61HP |
| Catalog number  | 10000           |
| Category        | Soft starter    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-4347C15EB9   |
| Generated       | 2026-08-06      |

## Product Overview

System: Soft Starter, Load: Phase 3, Housing width: >45mm to 90mm, Motor rating: >50kW to 80kW, Operational voltage: Up to 700VAC, Load current: >75A to 100A, Controlled phases: 2-Phase, Max number of stats per hour: >10 to 20, Communication: N/A, Load (result): Soft Starting of 3-Phase scroll compressors, Load current: 95A AC, Max motor rating: 75 kW, Operational voltage: 187 - 660V ACrms, Dimensions: 75 x 150 x 170 mm, Controlled phases: 2-Phase, Max number of stats per hour: 12

2Ph Comp.S/Start 220-600V 95A 24V I/P+Rly

3 phase soft starter for scroll compressors, Operating voltage (Ue): 220 - 600 Vac , Rated current (Ie): 95 Aac, Control voltage (Uc): 24 Vac/dc , DIN rail/Panel mount, Supply voltage (Us): 24 Vac/dc , 2-phase control

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

CARLO GAVAZZI &gt; Switches &gt; Frequency Drives and Limit

## Additional Product Information

## Specifications

Rated operation current Ie at 40 °C Tu95 ARated operating voltage Ue187 V ... 660 VRated power three-phase motor, inline, at 230 V22 kWRated power three-phase motor, inline, at 400 V55 kWRated control supply voltage Us at AC 50HZ21.6 V ... 26.4 VRated control supply voltage Us at DC0 V ... 0 VInternal bypassYesProduct Width75 mmProduct Height170 mmProduct Depth150 mm

ETIM for RSBD6095FFV61HP Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Rated operation current  $I_e$  at 40 °C  $T_u$  (EF007039)

95 A

Rated operating voltage  $U_e$  (EF002418)

187 V

Rated power three-phase motor, inline, at 230 V (EF007053)

22 kW

Rated power three-phase motor, inline, at 400 V (EF007054)

55 kW

Function (EF000030)

Single direction

Internal bypass (EF009214)

Yes

With display (EF000458)

No

Torque control (EF009215)

No

Rated surrounding temperature without derating (EF007074)

40 °C

Rated control supply voltage AC 50 Hz (EF003978)

21.6 V

Rated control supply voltage AC 60 Hz (EF003979)

21.6 V

Rated control supply voltage DC (EF003980)

0 V

Voltage type for actuating (EF008242)

AC/DC

Integrated motor overload protection (EF007297)

No

Release class (EF006668)

Other

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RSBD6095FFV61HP with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.