

## INDUSTRIAL COMPONENT DATA

# RSGD4045E0VX210 CARLO GAVAZZI System: Soft Starter, Load: Phase 3, Housing width: 22.5mm to 45mm, Motor rating: >20kW to 30kW

Brand: CARLO GAVAZZI | Manufacturer Part Number: RSGD4045E0VX210



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | CARLO GAVAZZI   |
| MPN / Reference | RSGD4045E0VX210 |
| Catalog number  | 10000           |
| Category        | Soft starter    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-2A8302F476   |
| Generated       | 2026-08-06      |

## Product Overview

System: Soft Starter, Load: Phase 3, Housing width: >22.5mm to 45mm, Motor rating: >20kW to 30kW, Operational voltage: Up to 480VAC, Load current: >32A to 50A, Controlled phases: 2-Phase, Max number of stats per hour: Up to 10, Communication: N/A, Load (result): Soft starter for 3-phase induction motors , Load current: 45A AC , Max motor rating: 22 kW , Operational voltage: 187 - 440V ACrms, Dimensions: 45 x 130 x 125 mm, Controlled phases: 2-Phase, Max number of stats per hour: 10

Starter three-phase, general purpose 2-phase controlled + 1 direct, Intensity Amp. 45, with sink

3 phase soft starter for induction motors, Operating voltage (Ue): 220 - 400 Vac , Rated current (Ie): 45 Aac, Control voltage (Uc): 110 - 400 Vac , DIN rail, Supply voltage (Us): Internal, 2-phase control, 2 relay outputs, Class 10 overload

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | CARLO GAVAZZI > Switches > Frequency Drives and Limit |
|--------------|-------------------------------------------------------|

## Additional Product Information

## Specifications

Rated operation current Ie at 40 °C Tu45 ARated operating voltage Ue187 V ... 440 VRated power three-phase motor, inline, at 230 V11 kWRated power three-phase motor, inline, at 400 V22 kWRated control supply voltage Us at AC 50HZ93.5 V ... 440 VRated control supply voltage Us at DC0 V ... 0 VInternal bypassYesProduct Width45 mmProduct Height149 mmProduct Depth137 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RSGD4045E0VX210 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.