

INDUSTRIAL COMPONENT DATA

RSGD6085FFVX310C CARLO GAVAZZI System: Soft Starter, Load: Phase 3, Housing width: 45mm to 90mm, Motor rating..

Brand: CARLO GAVAZZI | Manufacturer Part Number: RSGD6085FFVX310C



Manufacturer	CARLO GAVAZZI
MPN / Reference	RSGD6085FFVX310C
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-AF63003E4D
Generated	2026-08-06

Product Overview

System: Soft Starter, Load: Phase 3, Housing width: >45mm to 90mm, Motor rating: >50kW to 80kW, Operational voltage: Up to 700VAC, Load current: >75A to 100A, Controlled phases: 2-Phase, Max number of stats per hour: Up to 10, Communication: Modbus, Load (result): Soft starter for 3-phase induction motors , Load current: 85A AC, Max motor rating: 55 kW , Operational voltage: 187 - 660V ACrms, Dimensions: 75 x 177 x 206 mm, Controlled phases: 2-Phase, Max number of stats per hour: 10

Three-phase starter, general purpose 2 controlled phases + 1 direct, Current Amp. 85, Alim. External
3 phase soft starter for induction motors, Operating voltage (Ue): 220 - 600 Vac , Rated current (Ie): 85 Aac, Control voltage (Uc): 24 Vac/dc , DIN rail/Panel mount, Supply voltage (Us): 24 Vac/dc , 2-phase control, Class 10 overload, Modbus

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **CARLO GAVAZZI > Switches > Frequency Drives and Limit**

Additional Product Information

Specifications

Rated operation current Ie at 40 °C Tu85 ARated operating voltage Ue187 V ... 660 VRated power three-phase motor, inline, at 230 V22 kWRated power three-phase motor, inline, at 400 V45 kWRated control supply voltage Us at AC 50HZ21.6 V ... 26.4 VRated control supply voltage Us at DC21.6 V ... 26.4 VInternal bypassYesProduct Width75 mmProduct Height170 mmProduct Depth180 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RSGD6085FFVX310C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.