

INDUSTRIAL COMPONENT DATA

RSLM001048 CARLO GAVAZZI Electromechanical relay narrow 5 mm, Amperage 6 A, Voltage coil 48VDC, Configuratio..

Brand: CARLO GAVAZZI | Manufacturer Part Number: RSLM001048



Manufacturer	CARLO GAVAZZI
MPN / Reference	RSLM001048
Catalog number	001048
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-A1F36F0856
Generated	2026-08-06

Product Overview

Electromechanical relay narrow 5 mm, Amperage 6 A, Voltage coil 48VDC, Configuration SPDT

Slim Industrial Electromechanical Relays series, 6A 250VAC/30VDC, 5 poles, SPDT (1 Change Over contact), Coil voltage 48VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Switches > Industrials Relays and sockets
--------------	---

Additional Product Information

Specifications

Rated control supply voltage Us at AC 50HZ0 V ... 0 V
Rated control supply voltage Us at DC36 V ... 72 V
Nominal current6 A
Number of contacts as normally closed contact1
Number of contacts as normally open contact1
Number of contacts as change-over contact1
Type of electric connectionPCB connection; PCB connection
With LED indicationYes
Material contactBeryllium copper

ETIM for RSLM001048 Relays (EC001437)

Feature Name

Feature Value

Type of electric connection (EF003961)

PCB connection

With detachable clamps (EF003340)

No

Nominal current (EF000001)
6 A

Rated control supply voltage AC 50 Hz (EF003978)
0 V

Rated control supply voltage AC 60 Hz (EF003979)
0 V

Rated control supply voltage DC (EF003980)
36 V

Voltage type for actuating (EF008242)
DC

Drive, polarization (EF003355)
Polarity free

Drive, switching attitude (EF003356)
Mono stable

Number of contacts as normally closed contact (EF008255)
1

Number of contacts as normally open contact (EF008256)
1

Number of contacts as change-over contact (EF008257)
1

With forced-guided contacts (EF003357)
No

Type of switch contact (EF003358)
Double contact

Complete with socket (EF003359)
Yes

With LED indication (EF005950)
Yes

Material of contact surface (EF004020)
Untreated

Material of contact insert (EF008521)
Ceramics

Material contact (EF007544)
Beryllium copper

Degree of protection (IP) (EF005474)
IP20

Width (EF000008)
28 mm

Height (EF000040)
18.5 mm

Depth (EF000049)
5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RSLM001048 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.