

INDUSTRIAL COMPONENT DATA

CA18GLF08NA CARLO GAVAZZI Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING M18 SENSING RANGE 6 ..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CA18GLF08NA



Manufacturer	CARLO GAVAZZI
MPN / Reference	CA18GLF08NA
Catalog number	10000
Category	Capacitive proximity switch
Minimum order	1 Pcs
Document ID	EO-097D12A134
Generated	2026-08-04

Product Overview

Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING M18 SENSING RANGE >6 to 8 mm OUTPUT DC NPN SYSTEM Sensor Others HOUSING M18 x 87,0 mm SENSING RANGE 8 mm MATERIAL Pvc

Cylindrical capacitive potentiometer adjustment, Metric 18, Chemical resistant

Capacitive Proximity Sensor, Flush mountable, Sensing Range 8mm, Adjustable 3-8mm, Power Supply 10-40VDC, NPN Output, N.C. + N.O., Cable PVC, PVC Housing M18 x 71,5mm, Tripleshield, IP67

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Capacitive

Additional Product Information

Specifications

Rated operating distance8 mmInstallation TypeFlushDiameter18 mmOutput typeNPNOutput functionComplementary (NO+NC)Connection typeCableHousing typeCylindrical, threaded barrelHousing materialPlasticRated power supply10 V ... 40 VDegree of protectionIP67

ETIM for CA18GLF08NA Sensors (EC002715)

Feature Name

Feature Value

Width sensor (EF007094)

0 mm

Height of sensor (EF007283)
0 mm

Length of sensor (EF007334)
71.5 mm

Diameter sensor (EF007111)
18 mm

Mechanical mounting condition for sensor (EF004041)
Concise

Switching distance (EF003647)
8 mm

Suitable for safety functions (EF001597)
No

Type of switch function (EF003963)
Anticoincidence

Type of switching output (EF003962)
NPN

Type of electric connection (EF003961)
Cable

Number of semiconductor outputs with signalling function (EF003945)
0

Number of contact energized outputs with signalling function (EF003946)
0

Number of protected semiconductor outputs (EF003951)
2

Number of protected contact energized outputs (EF003952)
0

Type of actuation (EF006949)
Other

Type of interface (EF006977)
None

Type of interface for safety communication (EF003956)
None

Construction type housing (EF004008)
Cylinder, screw-thread

Coating housing (EF001601)
Other

Cascadable (EF000507)
No

SIL according to IEC 61508 (EF009889)
None

Performance level according to EN ISO 13849-1 (EF007399)
None

Max. output current at protected output (EF004035)
200 mA

Supply voltage (EF004127)
10 V

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / CA18GLF08NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.