

## INDUSTRIAL COMPONENT DATA

# CB32CLN20TCFTAX CARLO GAVAZZI Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING Ø32 SENSING RANG..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CB32CLN20TCFTAX



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | CARLO GAVAZZI               |
| MPN / Reference | CB32CLN20TCFTAX             |
| Catalog number  | 10000                       |
| Category        | Capacitive proximity switch |
| Minimum order   | 1 Pcs                       |
| Document ID     | EO-4D51EB77D7               |
| Generated       | 2026-08-01                  |

## Product Overview

Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING Ø32 SENSING RANGE >15 to 20 mm OUTPUT AC SCR SYSTEM Sensor Others HOUSING Ø32 x 101 mm SENSING RANGE 20 mm MATERIAL Thermoplastic Polyester

ATEX capacitive level probes, CB32 Series, For solids, liquids or granules, with TRIPLESIELD™

Capacitive Proximity Sensor, Non-flush mountable, Sensing Range 20mm, Adjustable 2-20mm, Power Supply 20-250VAC, SCR output N.C., On-delay 30s, Cable PVC, Housing 32 x 101mm, Tripleshield, IP67, Atex cat. 3D Dust

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path CARLO GAVAZZI &gt; Sensors &gt; Capacitive

## Additional Product Information

## Specifications

Rated operating distance20 mmInstallation TypeNon-FlushDiameter32 mmOutput typeTwo-wireOutput functionNormally Closed (NC)Connection typeCableHousing typeCylindrical, smooth barrelHousing materialPlasticRated power supply20 V ... 250 VDegree of protectionIP67

ETIM for CB32CLN20TCFTAX Sensors (EC002715)

Feature Name

Feature Value

Length of sensor (EF007334)

101 mm  
Diameter sensor (EF007111)  
32 mm  
Mechanical mounting condition for sensor (EF004041)  
Not flat  
Switching distance (EF003647)  
20 mm  
Suitable for safety functions (EF001597)  
No  
Type of switch function (EF003963)  
Breaker contact  
Type of switching output (EF003962)  
EV006725  
Type of electric connection (EF003961)  
Cable  
Number of semiconductor outputs with signalling function (EF003945)  
0  
Number of contact energized outputs with signalling function (EF003946)  
0  
Number of protected semiconductor outputs (EF003951)  
1  
Number of protected contact energized outputs (EF003952)  
0  
Type of actuation (EF006949)  
Other  
Type of interface (EF006977)  
None  
Type of interface for safety communication (EF003956)  
None  
Construction type housing (EF004008)  
Cylinder plain  
Coating housing (EF001601)  
Other  
Cascadable (EF000507)  
No  
SIL according to IEC 61508 (EF009889)  
None  
Performance level according to EN ISO 13849-1 (EF007399)  
None  
Max. output current at protected output (EF004035)  
500 mA  
Supply voltage (EF004127)  
20 V  
Rated control supply voltage AC 50 Hz (EF003978)  
20 V  
Rated control supply voltage AC 60 Hz (EF003979)  
20 V

Rated...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send CARLO GAVAZZI / CB32CLN20TCFTAX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.