

INDUSTRIAL COMPONENT DATA

EC5525NPAP CARLO GAVAZZI Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING Rectangular SENSING R..

Brand: CARLO GAVAZZI | Manufacturer Part Number: EC5525NPAP



Manufacturer	CARLO GAVAZZI
MPN / Reference	EC5525NPAP
Catalog number	10000
Category	Capacitive proximity switch
Minimum order	1 Pcs
Document ID	EO-78D556C623
Generated	2026-08-01

Product Overview

Selected parameters CONNECTION Cable MATERIAL Plastic HOUSING Rectangular SENSING RANGE >20 to 30 mm
OUTPUT DC NPN SYSTEM Sensor Others HOUSING 35 x 55 x 15 mm SENSING RANGE 25 mm MATERIAL
Polycarbonate

Capacitive, cable 2 m., Power supply 10-40 VDC, NPN output, NA/NC, Detection 25 mm.

Capacitive Proximity Sensor, Non-flush mountable, Sensing Range 25mm, Adjustable 4-25mm, Power Supply 10-40VDC,
NPN Output, N.O. and N.C., Cable PVC, Housing 35 x 15 x 55mm, Tripleshield, Improved EMC performances, IP67

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Capacitive

Additional Product Information

Specifications

Rated operating distance25 mmInstallation TypeNon-FlushOutput typeNPNOutput functionComplementary
(NO+NC)Connection typeCableHousing typeRectangularHousing materialPlasticRated power supply10 V ... 40 VDegree of
protectionIP67

ETIM for EC5525NPAP Sensors (EC002715)

Feature Name

Feature Value

Width sensor (EF007094)

35 mm
Height of sensor (EF007283)
15 mm
Length of sensor (EF007334)
55 mm
Diameter sensor (EF007111)
0 mm
Mechanical mounting condition for sensor (EF004041)
Not flat
Switching distance (EF003647)
25 mm
Suitable for safety functions (EF001597)
No
Type of switch function (EF003963)
Anticoincidence
Type of switching output (EF003962)
NPN
Type of electric connection (EF003961)
Cable
Number of semiconductor outputs with signalling function (EF003945)
0
Number of contact energized outputs with signalling function (EF003946)
0
Number of protected semiconductor outputs (EF003951)
2
Number of protected contact energized outputs (EF003952)
0
Type of actuation (EF006949)
Metallic Target
Type of interface (EF006977)
None
Type of interface for safety communication (EF003956)
None
Construction type housing (EF004008)
Cuboid
Coating housing (EF001601)
Other
Cascadable (EF000507)
No
SIL according to IEC 61508 (EF009889)
None
Performance level according to EN ISO 13849-1 (EF007399)
None
Max. output current at protected output (EF004035)
200 mA
Supply voltage (EF004127)
10 V

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated control supply voltage AC 60 Hz (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / EC5525NPAP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.