

INDUSTRIAL COMPONENT DATA

PCB01DM24 CARLO GAVAZZI Selected parameters

FUNCTION Asymmetrical recycler OUTPUT SIGNAL 2 relays

Others INP..

Brand: CARLO GAVAZZI | Manufacturer Part Number: PCB01DM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	PCB01DM24
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-C4168341EA
Generated	2026-08-02

Product Overview

Selected parameters FUNCTION Asymmetrical recycler OUTPUT SIGNAL 2 relays Others INPUT RANGE 0,1 s - 100 h
MOUNTING Plug-in SIZE 36 mm POWER SUPPLY RANGE 24÷240 V AC/DC SOCKET Circular
Timer, Asymmetric cyclic , Undecal base, P-box, 36 mm, DPDT 8A output
Asymmetrical recycler timer, time range 0.1 s - 100 h, automatic start, supply voltage 24-240 V AC/DC, 2 SPDT relay outputs, 36 mm plug-in housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Controls > Timers

Additional Product Information

Specifications

MountingPlug-inRecycler sub-functionAsymmetrical recycler; One shotOutput2 relaysDelay time rangeUp to 10s; Up to 60s; Up to 600s; Multi-rangeTerminalsFor Plug-inApprovals, marks, declarationfor Europe; for North America; for Australia
ETIM for PCB01DM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

Function delay-on energization (EF003374)

Yes

Function delay on de-energization (EF003401)

No

Function floating contact on energization (EF003378)

No

Function floating contact on de-energization (EF003402)

No

Function star-delta (EF003380)

No

Function pulse shaping (EF003403)

Yes

Function flashing, starting with pause, fixed time (EF003363)

No

Function flashing, starting with pulse, fixed time (EF003364)

No

Clock function, starting with pause, variable (EF003365)

Yes

Clock function, starting with pulse, variable (EF003366)

Yes

Remote operation possible (EF003361)

No

Suitable as remote control (EF003362)

No

Pluggable on auxiliary contact block (EF006952)

Yes

Rated control supply voltage AC 50 Hz (EF003978)

20.4 V

Rated control supply voltage AC 60 Hz (EF003979)

20.4 V

Rated control supply voltage DC (EF003980)

20.4 V

Voltage type for actuating (EF008242)

AC/DC

Time range (EF003384)

0.1 s

Number of outputs, delayed, change-over contact (EF006840)

2

Outputs, reversible delayed/undelayed (EF006988)

No

With semiconductor output (EF003373)

No

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

Width (EF0000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PCB01DM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.