

INDUSTRIAL COMPONENT DATA

PBA02CM24 CARLO GAVAZZI Selected parameters

FUNCTION Delay on release OUTPUT SIGNAL 1 relay Others

INPUT RAN..

Brand: CARLO GAVAZZI | Manufacturer Part Number: PBA02CM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	PBA02CM24
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-60B34C000E
Generated	2026-08-01

Product Overview

Selected parameters FUNCTION Delay on release OUTPUT SIGNAL 1 relay Others INPUT RANGE 0,1 s - 100 h
MOUNTING Plug-in SIZE 36 mm POWER SUPPLY RANGE 24÷240VAC and 24VDC SOCKET Circular
Disconnect Delay External Contact Control, Undecal Base Mount, P-Box, 36 mm
Timer Delay on release, Plug-in Socket mount, 36x80x94mm Euronorm housing, selectable time ranges 0,1s - 100h,
Supply voltage 24-240Vac and 24Vdc, 8A SPDT relay output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI
--------------	---------------

Additional Product Information

Specifications

MountingPlug-inTrigger inputManualOutput1 relayDelay time rangeUp to 10s; Up to 60s; Up to 600s; Multi-rangeApprovals,
marks, declarationfor Europe; for North America; for Australia

ETIM for PBA02CM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

Function delay-on energization (EF003374)

No
Function delay on de-energization (EF003401)
Yes
Function floating contact on energization (EF003378)
No
Function floating contact on de-energization (EF003402)
No
Function star-delta (EF003380)
No
Function pulse shaping (EF003403)
No
Function flashing, starting with pause, fixed time (EF003363)
No
Function flashing, starting with pulse, fixed time (EF003364)
No
Clock function, starting with pause, variable (EF003365)
No
Clock function, starting with pulse, variable (EF003366)
No
Remote operation possible (EF003361)
Yes
Suitable as remote control (EF003362)
No
Pluggable on auxiliary contact block (EF006952)
Yes
Rated control supply voltage AC 50 Hz (EF003978)
20.4 V
Rated control supply voltage AC 60 Hz (EF003979)
20.4 V
Rated control supply voltage DC (EF003980)
20.4 V
Voltage type for actuating (EF008242)
AC/DC
Time range (EF003384)
0.1 s
Number of outputs, delayed, change-over contact (EF006840)
1
Outputs, reversible delayed/undelayed (EF006988)
No
With semiconductor output (EF003373)
No
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Width (EF000008)
36 mm
Height (EF000040)
80 mm

Depth (EF000049)

94 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PBA02CM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.