

INDUSTRIAL COMPONENT DATA

DMB01DM24 CARLO GAVAZZI Selected parameters

FUNCTION Multi-function OUTPUT SIGNAL 2 relays Others

INPUT RANG..

Brand: CARLO GAVAZZI | Manufacturer Part Number: DMB01DM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	DMB01DM24
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-A025C31ACD
Generated	2026-07-31

Product Overview

Selected parameters FUNCTION Multi-function OUTPUT SIGNAL 2 relays Others INPUT RANGE 0,1 s - 100 h
MOUNTING DIN-rail SIZE 22,5 mm POWER SUPPLY RANGE 24÷240 V AC/DC SOCKET N/A

Timer, Multifunction, DIN rail, D-box, 22.5 mm, DPDT 8A output

Multifunctions timer, time range 0.1 s - 100 h, automatic or manual start, supply voltage 24-240 V AC/DC, DPDT relay outputs, 22.5 mm DIN-rail housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Timers
--------------	-----------------------------------

Additional Product Information

Specifications

MountingIndustrial DIN-railTrigger inputAutomatic; ManualInterval sub-functionDouble interval; Interval on trigger
openRecycler sub-functionSymmetrical recyclerOutput2 relays

ETIM for DMB01DM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Function delay-on energization (EF003374)

Yes

Function delay on de-energization (EF003401)

Yes

Function floating contact on energization (EF003378)

No

Function floating contact on de-energization (EF003402)

No

Function star-delta (EF003380)

No

Function pulse shaping (EF003403)

Yes

Function flashing, starting with pause, fixed time (EF003363)

No

Function flashing, starting with pulse, fixed time (EF003364)

No

Clock function, starting with pause, variable (EF003365)

Yes

Clock function, starting with pulse, variable (EF003366)

Yes

Remote operation possible (EF003361)

Yes

Suitable as remote control (EF003362)

No

Pluggable on auxiliary contact block (EF006952)

No

Rated control supply voltage AC 50 Hz (EF003978)

20.4 V

Rated control supply voltage AC 60 Hz (EF003979)

20.4 V

Rated control supply voltage DC (EF003980)

20.4 V

Voltage type for actuating (EF008242)

AC/DC

Time range (EF003384)

0.1 s

Number of outputs, delayed, change-over contact (EF006840)

2

Outputs, reversible delayed/undelayed (EF006988)

No

With semiconductor output (EF003373)

No

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

Width (EF000008)

22.5 mm

Height (EF000040)

80 mm

Depth (EF000049)

99.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DMB01DM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.