

INDUSTRIAL COMPONENT DATA

DBB51CM2410S CARLO GAVAZZI Selected parameters FUNCTION True delay on release OUTPUT SIGNAL 1 relay Others I..

Brand: CARLO GAVAZZI | Manufacturer Part Number: DBB51CM2410S



Manufacturer	CARLO GAVAZZI
MPN / Reference	DBB51CM2410S
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-9CF75C4ABD
Generated	2026-08-01

Product Overview

Selected parameters FUNCTION True delay on release OUTPUT SIGNAL 1 relay Others INPUT RANGE 1 s - 10 s
MOUNTING DIN-rail SIZE 17,5 mm POWER SUPPLY RANGE 24÷240VAC and 24VDC SOCKET N/A

Timer, True disconnect delay with condenser, DIN carriage, Mini D box, 17.5 mm

Timer True delay on release, DIN rail mount, 17,5x81x67,2mm housing, adjustable time settings 1s - 10s, Supply voltage 24-240Vac and 24Vdc, Screw terminals connection, 5A SPDT relay output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Timers
--------------	-----------------------------------

Additional Product Information

Specifications

MountingMini DIN-railTrigger inputAutomaticOutput1 relayDelay time rangeUp to 10sApprovals, marks, declarationfor Europe; for Australia

ETIM for DBB51CM2410S Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Function delay-on energization (EF003374)

No
Function delay on de-energization (EF003401)
Yes
Function floating contact on energization (EF003378)
No
Function floating contact on de-energization (EF003402)
No
Function star-delta (EF003380)
No
Function pulse shaping (EF003403)
No
Function flashing, starting with pause, fixed time (EF003363)
No
Function flashing, starting with pulse, fixed time (EF003364)
No
Clock function, starting with pause, variable (EF003365)
No
Clock function, starting with pulse, variable (EF003366)
No
Remote operation possible (EF003361)
No
Suitable as remote control (EF003362)
No
Pluggable on auxiliary contact block (EF006952)
No
Rated control supply voltage AC 50 Hz (EF003978)
20.4 V
Rated control supply voltage AC 60 Hz (EF003979)
20.4 V
Rated control supply voltage DC (EF003980)
20.4 V
Voltage type for actuating (EF008242)
AC/DC
Time range (EF003384)
1 s
Number of outputs, delayed, change-over contact (EF006840)
1
Outputs, reversible delayed/undelayed (EF006988)
No
With semiconductor output (EF003373)
No
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Width (EF000008)
17.5 mm
Height (EF000040)
81 mm

Depth (EF000049)

67.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DBB51CM2410S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.