

INDUSTRIAL COMPONENT DATA

PBB02DM24 CARLO GAVAZZI Selected parameters

FUNCTION True delay on release OUTPUT SIGNAL 2 relays

Others INP..

Brand: CARLO GAVAZZI | Manufacturer Part Number: PBB02DM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	PBB02DM24
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-F7859888E9
Generated	2026-08-02

Product Overview

Selected parameters FUNCTION True delay on release OUTPUT SIGNAL 2 relays Others INPUT RANGE 60 s - 10 h
MOUNTING Plug-in SIZE 36 mm POWER SUPPLY RANGE 24÷240 V AC/DC SOCKET Circular
Timer, True disconnection delay with battery, Base, P-box, 36 mm
Timer True Delay on release, Built-in battery, Plug-in Socket mount, 36x80x94mm Euronorm housing, selectable time ranges 60s - 10h, Supply voltage 24-240Vac/Vdc, 8A DPDT relay output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Timers
--------------	-----------------------------------

Additional Product Information

Specifications

MountingPlug-inTrigger inputAutomaticOutput2 relaysDelay time rangeUp to 10s; Up to 60s; Up to 600s; Up to 10h;
Multi-rangeApprovals, marks, declarationfor Europe; for Australia

ETIM for PBB02DM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

Function delay-on energization (EF003374)

No
Function delay on de-energization (EF003401)
Yes
Function floating contact on energization (EF003378)
No
Function floating contact on de-energization (EF003402)
No
Function star-delta (EF003380)
No
Function pulse shaping (EF003403)
No
Function flashing, starting with pause, fixed time (EF003363)
No
Function flashing, starting with pulse, fixed time (EF003364)
No
Clock function, starting with pause, variable (EF003365)
No
Clock function, starting with pulse, variable (EF003366)
No
Remote operation possible (EF003361)
No
Suitable as remote control (EF003362)
No
Pluggable on auxiliary contact block (EF006952)
No
Rated control supply voltage AC 50 Hz (EF003978)
20.4 V
Rated control supply voltage AC 60 Hz (EF003979)
20.4 V
Rated control supply voltage DC (EF003980)
20.4 V
Voltage type for actuating (EF008242)
AC/DC
Time range (EF003384)
60 s
Number of outputs, delayed, change-over contact (EF006840)
2
Outputs, reversible delayed/undelayed (EF006988)
No
With semiconductor output (EF003373)
No
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Width (EF000008)
36 mm
Height (EF000040)
80 mm

Depth (EF000049)

94 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PBB02DM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.