

INDUSTRIAL COMPONENT DATA

DBB01DM24 CARLO GAVAZZI Selected parameters

FUNCTION True delay on release OUTPUT SIGNAL 2 relays

Others INP..

Brand: CARLO GAVAZZI | Manufacturer Part Number: DBB01DM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	DBB01DM24
Catalog number	10000
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-7BE3708D13
Generated	2026-08-02

Product Overview

Selected parameters FUNCTION True delay on release OUTPUT SIGNAL 2 relays Others INPUT RANGE 0,1 s - 600 s
MOUNTING DIN-rail SIZE 22,5 mm POWER SUPPLY RANGE 24÷240 V AC/DC SOCKET N/A
Timer, True disconnect delay with condenser, DIN carriage, Box D, 22.5 mm
Timer True delay on release, DIN rail mount, 22,5x80x99,5mm Euronorm housing, selectable time ranges 0,1s - 10m,
Supply voltage 24-240Vac/Vdc, Screw terminals connection, 8A DPDT relay output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Timers
--------------	-----------------------------------

Additional Product Information

Specifications

MountingIndustrial DIN-railTrigger inputAutomaticOutput2 relaysDelay time rangeUp to 600sApprovals, marks,
declarationfor Europe; for Australia

ETIM for DBB01DM24 Relays (EC001439)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Function delay-on energization (EF003374)

No
Function delay on de-energization (EF003401)
Yes
Function floating contact on energization (EF003378)
No
Function floating contact on de-energization (EF003402)
No
Function star-delta (EF003380)
No
Function pulse shaping (EF003403)
No
Function flashing, starting with pause, fixed time (EF003363)
No
Function flashing, starting with pulse, fixed time (EF003364)
No
Clock function, starting with pause, variable (EF003365)
No
Clock function, starting with pulse, variable (EF003366)
No
Remote operation possible (EF003361)
No
Suitable as remote control (EF003362)
No
Pluggable on auxiliary contact block (EF006952)
No
Rated control supply voltage AC 50 Hz (EF003978)
20.4 V
Rated control supply voltage AC 60 Hz (EF003979)
20.4 V
Rated control supply voltage DC (EF003980)
20.4 V
Voltage type for actuating (EF008242)
AC/DC
Time range (EF003384)
0.1 s
Number of outputs, delayed, change-over contact (EF006840)
2
Outputs, reversible delayed/undelayed (EF006988)
No
With semiconductor output (EF003373)
No
Suitable for DIN rail (top hat rail) mounting (EF007250)
No
Width (EF000008)
22.5 mm
Height (EF000040)
80 mm

Depth (EF000049)

99.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DBB01DM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.