

INDUSTRIAL COMPONENT DATA

VMUCPVAWSSUX CARLO GAVAZZI Selected parameters FUNCTION Web Server for Eos-Array MOUNTING DIN-rail OUTPUT IN..

Brand: CARLO GAVAZZI | Manufacturer Part Number: VMUCPVAWSSUX



Manufacturer	CARLO GAVAZZI
MPN / Reference	VMUCPVAWSSUX
Catalog number	10000
Category	Photovoltaics data logger
Minimum order	1 Pcs
Document ID	EO-A23762D95A
Generated	2026-07-29

Product Overview

Selected parameters FUNCTION Web Server for Eos-Array MOUNTING DIN-rail OUTPUT INPUT PORT None
COMMUNICATION Ethernet, USB, RS485 Others RANGE None DISPLAY None VIARIABLES None NUMBER OF
INPUTS 4 NUMBER OF OUTPUTS None POWER SUPPLY 12 to 28VDC
Photovoltaic Plant Monitoring, Scada Solution
Web-Server, Datalogger, Gateway for Photovoltaic Monitoring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI
--------------	---------------

Additional Product Information

Energy Management Integrated WEB based monitoring solution for Solar PV applications Type Eos-Web

- Integrated modular local monitoring system for PV plants based on WEB access
- Up to 20 DIN modules configuration equivalent to 360mm width
- Eos-Web can manage on local bus up to 18 VMU units and up to 10 Eos-Array on RS485 bus.
- Eos-Web can manage in addition to VMU-C, WEB communication access master unit up to:
 - max 1 VMU-W unit

- max 15 VMU-S units
- max 1 VMU-P unit
- max 3 VMU-O units
- max 1 VMU-O.AT unit
- max 1 VMU-1.

Product Description

Eos-Web is a combination of modules which performs the monitoring of a roof-top photovoltaic installation or a ground small to medium size plant. The core unit is VMU-C which in addition to the data-logging, web server functionality performs also the local bus management of VMU-S, VMU-P both "Measuring units", VMU-O "I/O unit" and VMU-W "Modem unit". VMU-C assigns the proper local unit address automatically (up to 15 units). VMU-C can provide by means of a VMU-O module relay outputs alarm contacts and digital input status (e.g. to sense the tripping of the switch disconnector and the exhausting of the surge protection device). The VMU-W unit has the task to transmit, with wire-less modem technology, all the data when a wired LAN or Internet access is not available. Housing for DIN-rail mounting, IP40 (front) protection degree.

Specifications are subject to change without notice Eos-Web DS 1206151

ETIM for VMUCPVAWSSUX Renewable energy system...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / VMUCPVAWSSUX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.