

INDUSTRIAL COMPONENT DATA

SPPC24751 CARLO GAVAZZI Selected parameters MODEL AC to DC switching power supply AC INPUT VOLTAGE 90 264V O..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPPC24751



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPPC24751
Catalog number	24751
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-EBE87ED0AD
Generated	2026-08-05

Product Overview

Selected parameters MODEL AC to DC switching power supply AC INPUT VOLTAGE 90 - 264V OUTPUT POWER 75W
INPUT TYPE Single phase or DC OUTPUT VOLTAGE 24Vdc PFC no TERMINAL TYPE Screw terminal OUTPUT RDY no
Others DESCRIPTION ENCLOSED TYPE SWITCHING PS 24VDC 75W

Switching power supply, Output 24 VDC, Output current 3.2 A, Output power 75 W

Switching Power Supply, AC/DC, 75W, 24V, Screw Terminals, Enclosed type, with accessory for DIN-Rail Mounting,
Over-load, Over-voltage and Short-circuit Protections, 98x38x129mm metallic housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Power supplies

Additional Product Information

Specifications

Rated output voltage DC24 VPower output76.8 WMax. output current DC3.2 ATerminal typeScrew connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width98 mmHeight38 mmDepth129 mm
ETIM for SPPC24751 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

23.52 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

3.2 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

3.2 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

90 V

Rated supply voltage AC 60 Hz (EF007077)

90 V

Rated supply voltage DC (EF007078)

127 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

0 VA

Power output (EF003034)

76.8 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No
Modular version (EF001126)
No
Width in number of modular spacings (EF002950)
0
Built-in width (EF000846)
98 mm
Bui...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPPC24751 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.