

INDUSTRIAL COMPONENT DATA

SPM5BC1260 CARLO GAVAZZI Selected parameters MODEL Battery charger AC INPUT VOLTAGE 90 264V OUTPUT POWER 60W..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPM5BC1260



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPM5BC1260
Catalog number	10000
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-6774FCCB0C
Generated	2026-08-03

Product Overview

Selected parameters MODEL Battery charger AC INPUT VOLTAGE 90 - 264V OUTPUT POWER 60W PARALLEL CONNECTION no INPUT TYPE Single phase or DC OUTPUT VOLTAGE 12Vdc PFC no DC INPUT VOLTAGE 120 - 375V TERMINAL TYPE Screw terminal OUTPUT RDY no Others DESCRIPTION SPM battery Charger 12VDC 60W Modular Battery Charger, 12 VDC Output - Plastic Housing Low Profile Switching Power Supply Battery Charger, 1-phase, 12Vdc, 61W, DIN Rail Mounting, 5-DIN module

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Power supplies

Additional Product Information

Specifications

Rated output voltage DC12 VPower output61 WMax. output current DC4.5 ATerminal typeScrew connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width90 mmHeight91 mmDepth57 mm ETIM for SPM5BC1260 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

11.88 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

4.5 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

12 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

4.5 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

100 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Rated supply voltage DC (EF007078)

120 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

10.9 VA

Power output (EF003034)

61 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Width in number of modular spacings (EF002950)

0

Built-in width (EF000846)

90 mm

Bu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPM5BC1260 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.