

INDUSTRIAL COMPONENT DATA

SPD122401C CARLO GAVAZZI Selected parameters MODEL Din Rail AC INPUT VOLTAGE 88 264V OUTPUT POWER 240W PARAL..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPD122401C



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPD122401C
Catalog number	122401
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-E2D23B9B6B
Generated	2026-08-05

Product Overview

Selected parameters MODEL Din Rail AC INPUT VOLTAGE 88 - 264V OUTPUT POWER 240W PARALLEL CONNECTION yes INPUT TYPE Single phase or DC OUTPUT VOLTAGE 12Vdc PFC yes DC INPUT VOLTAGE 120 - 375V TERMINAL TYPE Screw terminal OUTPUT RDY Relay SPST Others DESCRIPTION 240W, Screw terminals, PFC, Parallel function

Spd12-240-1C(Power Supply)

Switching Power Supply, AC/DC, 240W, 12V, Screw Terminals, IP20, DIN-Rail Mounting, Over-load, Over-voltage, Short-circuit and Over-temperature Protections, 64x124.5x123,6mm metallic compact housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI
--------------	---------------

Additional Product Information

Specifications

Rated output voltage DC12 VPower output192 WMax. output current DC16 ATerminal typeScrew connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP00Width64 mmHeight124.5 mmDepth123.6 mm

ETIM for SPD122401C Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

11.88 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

16 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

12 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

16 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

100 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Rated supply voltage DC (EF007078)

120 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

19 VA

Power output (EF003034)

192 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Width in number of modular spacings (EF002950)

0

Built-in width (EF000846)

64 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPD122401C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.