

INDUSTRIAL COMPONENT DATA

SPD24051 CARLO GAVAZZI Selected parameters MODEL Din Rail AC INPUT VOLTAGE 90 265V OUTPUT POWER 5W PARALLEL ..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPD24051



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPD24051
Catalog number	24051
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-D9810A08DF
Generated	2026-08-02

Product Overview

Selected parameters MODEL Din Rail AC INPUT VOLTAGE 90 - 265V OUTPUT POWER 5W PARALLEL CONNECTION
no INPUT TYPE Single phase or DC OUTPUT VOLTAGE 24Vdc PFC no DC INPUT VOLTAGE 120 - 370V TERMINAL
TYPE Screw terminal OUTPUT RDY no Others DESCRIPTION 5W, Screw terminals
Single-phase power supply, output 24 Vdc, output current 0.21 A, output power 5 W
Switching Power Supply, AC/DC, 5W, 24V, Screw Terminals, IP20, DIN-Rail Mounting, Over-load, Over-voltage and
Short-circuit Protections, 22.5x90x114mm housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Power supplies

Additional Product Information

Specifications

Rated output voltage DC24 VPower output5 WMax. output current DC0.21 ATerminal typeInsulation piercing
connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width22.5 mmHeight90
mmDepth114 mm

ETIM for SPD24051 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

23.52 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

0.21 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

0.21 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

100 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Rated supply voltage DC (EF007078)

120 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

1.8 VA

Power output (EF003034)

5 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Insulation piercing connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Width in number of modular spacings (EF002950)

0

Built...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPD24051 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.