

INDUSTRIAL COMPONENT DATA

SPD242401B CARLO GAVAZZI Selected parameters MODEL Din Rail AC INPUT VOLTAGE 93 264V OUTPUT POWER 240W PARAL..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPD242401B



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPD242401B
Catalog number	242401
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-DF4CC5DCA5
Generated	2026-08-04

Product Overview

Selected parameters MODEL Din Rail AC INPUT VOLTAGE 93 - 264V OUTPUT POWER 240W PARALLEL CONNECTION yes INPUT TYPE Single phase or DC OUTPUT VOLTAGE 24Vdc PFC yes DC INPUT VOLTAGE 210 - 370V TERMINAL TYPE Removable connector OUTPUT RDY Relay SPST Others DESCRIPTION 240W, Removable connector, PFC, Parallel function, RDY out

Spd24-2401B (Power Supply)

Switching Power Supply, AC/DC, 240W, 24V, Plug-in Connectors, IP20, DIN-Rail Mounting, Over-load, Over-voltage and Short-circuit Protections, 83.5x143.5x123,6mm metallic housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI
--------------	---------------

Additional Product Information

Specifications

Rated output voltage DC24 VPower output240 WMax. output current DC10 ATerminal typePlug-in connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width83.5 mmHeight143.5 mmDepth123.6 mm
ETIM for SPD242401B Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

23.76 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

10 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

10 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

115 V

Rated supply voltage AC 60 Hz (EF007077)

115 V

Rated supply voltage DC (EF007078)

210 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

35 VA

Power output (EF003034)

240 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Plug-in connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Width in number of modular spacings (EF002950)

0

Built-in width (EF000846)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPD242401B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.