

INDUSTRIAL COMPONENT DATA

EI1202NPOPL CARLO GAVAZZI Selected parameters OUTPUT FUNCTION NO MOUNTING Flush HOUSING M12 SENSING RANGE up..

Brand: CARLO GAVAZZI | Manufacturer Part Number: EI1202NPOPL



Manufacturer	CARLO GAVAZZI
MPN / Reference	EI1202NPOPL
Catalog number	10000
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-C37405A282
Generated	2026-08-01

Product Overview

Selected parameters OUTPUT FUNCTION NO MOUNTING Flush HOUSING M12 SENSING RANGE up to 2 mm OUTPUT DC NPN CONNECTION Cable WIRE 3-wire MATERIAL Plastic SYSTEM Proximity Sensor Others HOUSING M12 x 50 mm MATERIAL Plastic SENSING RANGE 2 mm OUTPUT FUNCTION Normally Open

Ind Prox PI M12 Npn No,Cab

Inductive proximity sensor, M12 Thermoplastic., 2m cable, Sn 2mm, Flush mount, Long body, NPN NO, Supply voltage 10-32Vdc, Max output current 200 mA, Max switching frequency 800Hz, Operating temperature -25C - +70C, IP67.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI
--------------	---------------

Additional Product Information

Specifications

Rated operating distance2 mmInstallation typeFlushDiameterM12Output typeNPNOutput functionNormally Open

(NO)Connection typeCableHousing materialPlasticRated power supply10 V ... 32 V

ETIM for EI1202NPOPL Sensors (EC002714)

Feature Name

Feature Value

Length of sensor (EF007334)

50 mm

Diameter sensor (EF007111)
12 mm
Mechanical mounting condition for sensor (EF004041)
Concise
Switching distance (EF003647)
2 mm
Type of switch function (EF003963)
Normally open contact
Type of switching output (EF003962)
NPN
Type of electric connection (EF003961)
Cable
Number of protected semiconductor outputs (EF003951)
1
Type of actuation (EF006949)
Metallic Target
Cascadable (EF000507)
No
Max. output current at protected output (EF004035)
200 mA
Supply voltage (EF004127)
10 V
Rated control supply voltage DC (EF003980)
10 V
Voltage type (EF000187)
DC
Switching frequency (EF003587)
800 Hz
With monitoring function downstream switching devices (EF004052)
No
Housing material (EF001596)
Plastic
Compression-resistant (EF007106)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / EI1202NPOPL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.