

## INDUSTRIAL COMPONENT DATA

# EI1204NPOSL-1 CARLO GAVAZZI Selected parameters OUTPUT FUNCTION NO MOUNTING Non Flush HOUSING M12 SENSING RA..

Brand: CARLO GAVAZZI | Manufacturer Part Number: EI1204NPOSL-1



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | CARLO GAVAZZI              |
| MPN / Reference | EI1204NPOSL-1              |
| Catalog number  | 10000                      |
| Category        | Inductive proximity switch |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-5DB1684660              |
| Generated       | 2026-08-05                 |

## Product Overview

Selected parameters OUTPUT FUNCTION NO MOUNTING Non Flush HOUSING M12 SENSING RANGE >2 to 4 mm  
OUTPUT DC NPN CONNECTION Plug WIRE 3-wire MATERIAL Metal SYSTEM Proximity Sensor Others HOUSING M12 x  
66 mm MATERIAL Stainless steel SENSING RANGE 4 mm OUTPUT FUNCTION Normally Open

Inductive Proximity Sensors

Inductive proximity sensor, M12 Stainless steel, M12 plug, Sn 4mm, Non- Flush mount, Long body, NPN NO, Supply  
voltage 10-32Vdc, Max output current 200 mA, Max switching frequency 500Hz, Operating temperature -25C - +70C, IP67

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Inductive and Loop Detector

## Additional Product Information

Specifications

Rated operating distance4 mmInstallation typeFlushDiameterM12Output typeNPNOOutput functionNormally Open  
(NO)Connection typePlug-in connectionHousing typeCylindrical, threaded barrelHousing materialMetalRated power  
supply10 V ... 32 V

ETIM for EI1204NPOSL-1 Sensors (EC002714)

Feature Name

Feature Value

Length of sensor (EF007334)

50 mm  
Diameter sensor (EF007111)  
12 mm  
Mechanical mounting condition for sensor (EF004041)  
Concise  
Switching distance (EF003647)  
4 mm  
Type of switch function (EF003963)  
Normally open contact  
Type of switching output (EF003962)  
NPN  
Type of electric connection (EF003961)  
Plug-in connection  
Number of protected semiconductor outputs (EF003951)  
1  
Type of actuation (EF006949)  
Metallic Target  
Construction type housing (EF004008)  
Cylinder, screw-thread  
Max. output current at protected output (EF004035)  
200 mA  
Supply voltage (EF004127)  
10 V  
Rated control supply voltage DC (EF003980)  
10 V  
Voltage type (EF000187)  
DC  
Switching frequency (EF003587)  
500 Hz  
Housing material (EF001596)  
Metal

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / EI1204NPOSL-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.