

## INDUSTRIAL COMPONENT DATA

# ICB12S30N04PO CARLO GAVAZZI Selected parameters OUTPUT FUNCTION NO MOUNTING Non Flush HOUSING M12 SENSING RA..

Brand: CARLO GAVAZZI | Manufacturer Part Number: ICB12S30N04PO



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | CARLO GAVAZZI              |
| MPN / Reference | ICB12S30N04PO              |
| Catalog number  | 10000                      |
| Category        | Inductive proximity switch |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-703756663B              |
| Generated       | 2026-08-02                 |

## Product Overview

Selected parameters OUTPUT FUNCTION NO MOUNTING Non Flush HOUSING M12 SENSING RANGE >2 to 4 mm  
OUTPUT DC PNP CONNECTION Cable WIRE 3-wire MATERIAL Metal SYSTEM Proximity Sensor Others HOUSING M12  
x 51 mm MATERIAL Nichel Plated Brass SENSING RANGE 4 mm OUTPUT FUNCTION Normally Open  
Inductive M12 standard reach short box, cable 2 m, non-flush mounting, detection 4 mm, PNP NA  
Inductive proximity sensor, M12 Nickel-Plated Brass, 2m cable, Sn 4mm, Non-Flush mount, Short body, PNP NO output,  
Supply voltage 10-36Vdc, Max output current 200 mA, Max switching frequency 2 kHz, Operating temperature -25C - +70C,  
IP67

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path CARLO GAVAZZI &gt; Sensors &gt; Inductive and Loop Detector

## Additional Product Information

## Specifications

Rated operating distance4 mmInstallation typeNon-flushDiameterM12Output typePNPOutput functionNormally Open  
(NO)Connection typeCableHousing typeCylindrical, threaded barrelHousing materialMetalRated power supply10 V ... 36 V  
ETIM for ICB12S30N04PO Sensors (EC002714)

Feature Name

Feature Value

Width sensor (EF007094)

0 mm  
Height of sensor (EF007283)  
0 mm  
Length of sensor (EF007334)  
50.8 mm  
Diameter sensor (EF007111)  
12 mm  
Mechanical mounting condition for sensor (EF004041)  
Not flat  
Switching distance (EF003647)  
4 mm  
Suitable for safety functions (EF001597)  
No  
Type of switch function (EF003963)  
Normally open contact  
Type of switching output (EF003962)  
PNP  
Type of electric connection (EF003961)  
Cable  
Number of semiconductor outputs with signalling function (EF003945)  
1  
Number of contact energized outputs with signalling function (EF003946)  
0  
Number of protected semiconductor outputs (EF003951)  
0  
Number of protected contact energized outputs (EF003952)  
0  
Type of actuation (EF006949)  
Metallic Target  
Type of interface (EF006977)  
None  
Type of interface for safety communication (EF003956)  
None  
Construction type housing (EF004008)  
Cylinder, screw-thread  
Coating housing (EF001601)  
Nickel-plated  
Cascadable (EF000507)  
No  
SIL according to IEC 61508 (EF009889)  
None  
Performance level according to EN ISO 13849-1 (EF007399)  
None  
Max. output current at protected output (EF004035)  
200 mA  
Supply voltage (EF004127)  
10 V

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / ICB12S30N04PO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.