

INDUSTRIAL COMPONENT DATA

DPC02DM69 CARLO GAVAZZI Selected parameters OUTPUT SIGNAL 2 relays SETPOINTS 2, adjustable MONITORED VARIABLE..

Brand: CARLO GAVAZZI | Manufacturer Part Number: DPC02DM69



Manufacturer	CARLO GAVAZZI
MPN / Reference	DPC02DM69
Catalog number	10000
Category	Phase monitoring relay
Minimum order	1 Pcs
Document ID	EO-0967FC0641
Generated	2026-08-02

Product Overview

Selected parameters OUTPUT SIGNAL 2 relays SETPOINTS 2, adjustable MONITORED VARIABLE 3-phase AC voltage and frequency monitoring Others SIZE 45 mm POWER SUPPLY RANGE 600÷690 VAC MONITORING FUNCTION Under and over voltage/frequency, phase sequence, phase loss MOUNTING DIN-rail INPUT RANGE 600÷690 VAC DELAY 2, adjustable OTHERS VLN monitoring

Three-phase control relay of max. and min. voltage, max./min. frequency, sequence and phase loss

3-phase monitoring relay for phase loss, sequence, over and undervoltage, over and underfrequency, nominal range 600-690 V AC, delay on alarm 0.1-30 s, 2 SPDT relay outputs, 45 mm DIN-rail housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Controls > Monitoring Relays and Measurement Current Transformers
--------------	---

Additional Product Information

Specifications

MountingIndustrial DIN-railFunctionPhase loss; Phase sequence; Overvoltage; Undervoltage; Frequency3-phase voltage range600-690 VacFrequency range50-60 HzOutput2 relaysTime delayDelay on alarmApprovals, marks, declarationfor Europe; for North America; for China; for AustraliaSetting method through NFCNo

ETIM for DPC02DM69 Relays (EC001441)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

With detachable clamps (EF003340)

No

Phase sequence monitoring (EF003412)

Yes

Phase failure detection (EF003413)

Yes

Function under voltage detection (EF003414)

Yes

Function over voltage detection (EF003415)

Yes

Phase imbalance monitoring (EF003416)

No

Min. adjustable delay-on energization time (EF008190)

0.1 s

Max. permitted delay-on energization time (EF008189)

30 s

Width (EF000008)

45 mm

Height (EF000040)

80 mm

Depth (EF000049)

99.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / DPC02DM69 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.