

## INDUSTRIAL COMPONENT DATA

# VP01E CARLO GAVAZZI Selected parameters SYSTEM Level HOUSING 3/8" pipe tread SENSING RANGE Contact CONNECTIO..

Brand: CARLO GAVAZZI | Manufacturer Part Number: VP01E



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | CARLO GAVAZZI                           |
| MPN / Reference | VP01E                                   |
| Catalog number  | 10000                                   |
| Category        | Diffuse reflective photoelectric sensor |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-6A1E978FF2                           |
| Generated       | 2026-08-05                              |

## Product Overview

Selected parameters SYSTEM Level HOUSING 3/8" pipe tread SENSING RANGE Contact CONNECTION Cable OUTPUT DC NPN MATERIAL Plastic Others SENSING RANGE Direct detection HOUSING 3/8" x 74 mm MATERIAL Polysulphone Optical Level Probe, NPN Output, NC, Unmodulated Infrared Light for Liquid Detection  
Sensor for liquid level detection. High chemical resistance. Infrared light. Polysulphone housing. Ambient light 0 - 100 lux. NPN, NC, 10-40 VDC, 2 m PVC Cable. IP67

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | CARLO GAVAZZI > Sensors > Photoelectric |
|--------------|-----------------------------------------|

## Additional Product Information

## Specifications

Rated operating distance0 mm ... 0 mmOutput typeNPNOutput functionNormally Closed (NC)Connection  
TypeCableHousing typeCylindrical, threaded barrelHousing materialPlasticType of emitted lightInfrared lightSensing  
modeDark switchingDegree of protectionIP67Rated power supply10 V ... 40 V  
ETIM for VP01E Sensors (EC001821)

Feature Name

Feature Value

Pre failure notice (EF004129)

No

With time function (EF003582)  
No  
Max. switching distance (EF007367)  
0 mm  
Max. output current (EF001315)  
200 mA  
Number of semiconductor outputs with signalling function (EF003945)  
2  
Number of protected semiconductor outputs (EF003951)  
2  
Type of electric connection (EF003961)  
Cable  
Type of switching output (EF003962)  
NPN  
Type of switch function (EF003963)  
Breaker contact (NC)  
Construction type housing (EF004008)  
Cylinder, screw-thread  
Width sensor (EF007094)  
0 mm  
Diameter sensor (EF007111)  
27 mm  
Height of sensor (EF007283)  
0 mm  
Length of sensor (EF007334)  
74 mm  
Sensing mode (EF007503)  
Dark switching  
Material of optical surface (EF004134)  
Plastic  
Housing material (EF001596)  
Plastic  
Max. output current at protected output (EF004035)  
200 mA  
Response time (EF004094)  
16 ms  
Switching frequency (EF003587)  
30 Hz  
Voltage type (EF000187)  
DC  
With monitoring function downstream switching devices (EF004052)  
No  
Wavelength of the sensor (EF004132)  
0 nm  
Type of light (EF004029)  
Infrared light  
Light dot (EF004030)

0 mm<sup>2</sup>

AWG-number (EF007010)

0

Material of cable sheath (EF004136)

Polyurethane (PUR)

With res...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / VP01E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.