

INDUSTRIAL COMPONENT DATA

ILSP8 CARLO GAVAZZI Selected parameters SYSTEM Level HOUSING Smooth barrel OUTPUT Normally Open, Normally Cl..

Brand: CARLO GAVAZZI | Manufacturer Part Number: ILSP8



Manufacturer	CARLO GAVAZZI
MPN / Reference	ILSP8
Catalog number	10000
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-26D6E07EEE
Generated	2026-08-05

Product Overview

Selected parameters SYSTEM Level HOUSING Smooth barrel OUTPUT Normally Open, Normally Closed MATERIAL

Plastic Others HOUSING Ø44 CONTACT RATINGS 1500VAC, 3A, 120VA

Magnetic level sensor with float Ø 44 mm., plastic, Output NA, NC

Level magnetic sensor, Cylindrical plastic housing, 0.5m cable, NC or NO output reed contact, , Max switching voltage 1500 Vac, Max switching current 3A, Max switching power 120 VA, Operating temp. -25C - +100C, IP68.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Magnetic and Safety Magnetic
--------------	--

Additional Product Information

Specifications

Output typeReed switchMax switching current3000 mAConnection typeCableDegree of protectionIP68

ETIM for ILSP8 Sensors (EC002544)

Feature Name

Feature Value

Number of protected contact energized outputs (EF003952)

1

Type of actuation (EF006949)

Magnet

Type of electric connection (EF003961)

Cable

Type of switching output (EF003962)

Dry reed contact

Length of sensor (EF007334)

70 mm

Diameter sensor (EF007111)

44 mm

Housing material (EF001596)

Plastic

Max. output current at protected output (EF004035)

3000 mA

Ambient temperature (EF002386)

-25 °C

Rated supply voltage AC 50 Hz (EF007076)

0 V

Rated supply voltage AC 60 Hz (EF007077)

0 V

Voltage type (EF000187)

AC

Degree of protection (IP) (EF005474)

IP68

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / ILSP8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.