

INDUSTRIAL COMPONENT DATA

RR2A48FA550 CARLO GAVAZZI Selected parameters SYSTEM Motor Reversing LOAD Phase 3 HOUSING WIDTH 45mm to 90mm..

Brand: CARLO GAVAZZI | Manufacturer Part Number: RR2A48FA550



Manufacturer	CARLO GAVAZZI
MPN / Reference	RR2A48FA550
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-0A37DB6821
Generated	2026-08-04

Product Overview

Selected parameters SYSTEM Motor Reversing LOAD Phase 3 HOUSING WIDTH >45mm to 90mm MOTOR RATING Up to 3kW OPERATIONAL VOLTAGE Up to 550VAC LOAD CURRENT Up to 10A CONTROLLED PHASES 2-Phase MAX NUMBER OF STATS PER HOUR >40 to 50 Others LOAD (result) 2-Phase motor reversing controller with DC control LOAD CURRENT 11A AC MAX MOTOR RATING 5.5 kW OPERATIONAL VOLTAGE 40-530V ACrms DIMENSIONS 103 x 73.5 x 41 mm CONTROLLED PHASES 2-Phase MAX NUMBER OF STATS PER HOUR 40
Static relay, motor inverter 480 VAC - 5.5 kW; Control voltage 10-40 VDC
3 phase motor reversing relay, Operating voltage (Ue): 480 Vac , Rated current (Ie): 11 Aac, Control voltage (Uc): 24 Vac, Panel mount

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Switches > Frequency Drives and Limit
--------------	---

Additional Product Information

Specifications

Rated operation current Ie at 40 °C Tu11 A Rated operating voltage Ue 40 V ... 530 V Rated power three-phase motor, inline, at 400 V 5.5 kW Rated control supply voltage Us at AC 50 Hz 0 V ... 0 V Rated control supply voltage Us at DC 0 V ... 0 V Internal bypass No Product Width 103 mm Product Height 73.5 mm Product Depth 41 mm
ETIM for RR2A48FA550 Low-voltage industrial controls and switchgear (EC000640)
Feature Name

Feature ValueRated operation current I_e at 40 °C T_u (EF007039)

11 A

Rated operating voltage U_e (EF002418)

40 V

Rated power three-phase motor, inline, at 400 V (EF007054)

5.5 kW

Function (EF000030)

Reversing starter

Internal bypass (EF009214)

No

With display (EF000458)

No

Torque control (EF009215)

No

Rated surrounding temperature without derating (EF007074)

40 °C

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated control supply voltage AC 60 Hz (EF003979)

0 V

Rated control supply voltage DC (EF003980)

0 V

Voltage type for actuating (EF008242)

DC

Integrated motor overload protection (EF007297)

No

Release class (EF006668)

Other

Degree of protection (IP) (EF005474)

IP10

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / RR2A48FA550 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.