

INDUSTRIAL COMPONENT DATA

FMMA3 CARLO GAVAZZI Selected parameters SYSTEM Proximity HOUSING M8 OUTPUT 1 Normally Open MATERIAL Stainles..

Brand: CARLO GAVAZZI | Manufacturer Part Number: FMMA3



Manufacturer	CARLO GAVAZZI
MPN / Reference	FMMA3
Catalog number	10000
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-5AB5AFAB12
Generated	2026-08-04

Product Overview

Selected parameters SYSTEM Proximity HOUSING M8 OUTPUT 1 Normally Open MATERIAL Stainless Steel SENSING RANGE >20 to 30 mm Others HOUSING M8 CONTACT RATINGS 500VAC, 0.5A, 10VA SWITCHING DISTANCE 27 mm Magnetic proximity sensor in cylindrical box and stainless steel body

Proximity magnetic sensors, Cylindrical stainless housing M8, 2m cable, Reed NO output, Max switching voltage 500Vac , Max switching current 500mA, Max switching power 10VA/W, Max switching distance 27mm, Operating temperature -25C - +75C, IP67.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Magnetic and Safety Magnetic
--------------	--

Additional Product Information

Specifications

Output typeReed switchMax switching current500 mAConnection typeCableHousing typeCylindrical, threaded barrelDegree of protectionIP67

ETIM for FMMA3 Sensors (EC002544)

Feature Name

Feature Value

Number of protected contact energized outputs (EF003952)

1

Type of actuation (EF006949)
Magnet
Type of electric connection (EF003961)
Cable
Type of switching output (EF003962)
Dry reed contact
Length of sensor (EF007334)
45 mm
Diameter sensor (EF007111)
8 mm
Construction type housing (EF004008)
Cylinder, screw-thread
Housing material (EF001596)
Stainless steel
Max. output current at protected output (EF004035)
500 mA
Ambient temperature (EF002386)
-25 °C
Mechanical mounting condition for sensor (EF004041)
Concise
Rated supply voltage AC 50 Hz (EF007076)
0 V
Rated supply voltage AC 60 Hz (EF007077)
0 V
Voltage type (EF000187)
AC
Switching distance (EF003647)
27 mm
Degree of protection (IP) (EF005474)
IP67

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / FMMA3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.