

INDUSTRIAL COMPONENT DATA

FMC3 CARLO GAVAZZI Selected parameters SYSTEM Proximity HOUSING Smooth barrel OUTPUT 1 Normally Closed MATER..

Brand: CARLO GAVAZZI | Manufacturer Part Number: FMC3



Manufacturer	CARLO GAVAZZI
MPN / Reference	FMC3
Catalog number	10000
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-559C41BDD7
Generated	2026-08-04

Product Overview

Selected parameters SYSTEM Proximity HOUSING Smooth barrel OUTPUT 1 Normally Closed MATERIAL Plastic SENSING RANGE >10 to 20 mm Others HOUSING Ø9.3 CONTACT RATINGS 500VAC, 0.5A, 10VA SWITCHING DISTANCE 20 mm

Magnetic proximity sensor in cylindrical box and plastic body

Proximity magnetic sensors, Cilindrical plastic housing M9.3, 0.5m cable, Reed NC output, Max switching voltage 500 Vac, Max switching current 500mA, Max switching power 5VA, Max switching distance 20 mm, Operating temperature -25C - +70C, IP67.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Magnetic and Safety Magnetic

Additional Product Information

Specifications

Output typeReed switchMax switching current500 mAConnection typeCableHousing typeCylindrical, threaded barrelDegree of protectionIP67

ETIM for FMC3 Sensors (EC002544)

Feature Name

Feature Value

Number of protected contact energized outputs (EF003952)

1

Type of actuation (EF006949)

Magnet

Type of electric connection (EF003961)

Cable

Type of switching output (EF003962)

Dry reed contact

Length of sensor (EF007334)

32 mm

Diameter sensor (EF007111)

9.3 mm

Construction type housing (EF004008)

Cylinder, screw-thread

Housing material (EF001596)

Plastic

Max. output current at protected output (EF004035)

500 mA

Ambient temperature (EF002386)

-25 °C

Mechanical mounting condition for sensor (EF004041)

Concise

Rated supply voltage AC 50 Hz (EF007076)

0 V

Rated supply voltage AC 60 Hz (EF007077)

0 V

Voltage type (EF000187)

AC

Switching distance (EF003647)

20 mm

Degree of protection (IP) (EF005474)

IP67

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / FMC3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.