

## INDUSTRIAL COMPONENT DATA

# PA18CAR65PAM1SA CARLO GAVAZZI Selected parameters SYSTEM Retro-reflective HOUSING M18 SENSING RANGE 6 ... 20..

Brand: CARLO GAVAZZI | Manufacturer Part Number: PA18CAR65PAM1SA



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | CARLO GAVAZZI                        |
| MPN / Reference | PA18CAR65PAM1SA                      |
| Catalog number  | 10000                                |
| Category        | Retroreflective photoelectric sensor |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-6ADC65034C                        |
| Generated       | 2026-08-04                           |

## Product Overview

Selected parameters SYSTEM Retro-reflective HOUSING M18 SENSING RANGE 6 ... 20 m CONNECTION M12 plug DC OUTPUT DC PNP MATERIAL Plastic Others SENSING RANGE 6,5 m HOUSING M18 x 43,8 mm MATERIAL ABS Photocell reflection on non-polarized mirror, Metric 18, DC, PBTP box, potentiometer adjustment Retro-reflective Photoelectric Sensor, Range 6500mm, infrared modulated light 850nm, Power Supply 10-30VDC, PNP Output, NO and NC, Light and Dark Switching, M12 Plug, IP67 IP69K, ECOLAB

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | CARLO GAVAZZI > Sensors > Photoelectric |
|--------------|-----------------------------------------|

## Additional Product Information

## Specifications

Rated operating distance6500 mmOutput typePNPOutput functionComplementary (NO+NC)Connection TypeConnector M12Housing styleCylindrical, threaded barrelHousing MaterialPlasticType of lightInfrared lightSensing modeLight-/dark switchingDegree of protectionIP67, IP69KRated Operetional voltage UB at DC10 V ... 30 V  
ETIM for PA18CAR65PAM1SA Sensors (EC002717)

Feature Name

Feature Value

Pre failure notice (EF004129)

No

With time function (EF003582)

No

Rated switching distance (EF008289)

6500 mm

Max. switching distance (EF007367)

6500 mm

Max. output current (EF001315)

100 mA

With reflector (EF007448)

No

Analogue output 0 V ... 10 V (EF006807)

No

Analogue output 0 mA ... 20 mA (EF006808)

No

Analogue output 4 mA ... 20 mA (EF006810)

No

Analogue output -10 V ... +10 V (EF006809)

No

With other analogue output (EF007485)

No

Setting procedure (EF003994)

Manual adjustment

With communication interface analogue (EF007305)

No

With communication interface AS-Interface (EF007306)

No

With communication interface CANOpen (EF007307)

No

With communication interface DeviceNet (EF007308)

No

With communication interface Ethernet (EF007309)

No

With communication interface INTERBUS (EF007310)

No

With communication interface PROFIBUS (EF007311)

No

With communication interface RS-232 (EF007312)

No

With communication interface RS-422 (EF007313)

No

With communication interface RS-485 (EF007314)

No

With communication interface SSD (EF007315)

No

With communication interface SSI (EF007316)

No

Nu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PA18CAR65PAM1SA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.