

INDUSTRIAL COMPONENT DATA

UA12BLD02PPM1TR CARLO GAVAZZI Selected parameters SYSTEM Sensor HOUSING M12 SENSING RANGE up to 0,2 m CONNEC..

Brand: CARLO GAVAZZI | Manufacturer Part Number: UA12BLD02PPM1TR



Manufacturer	CARLO GAVAZZI
MPN / Reference	UA12BLD02PPM1TR
Catalog number	10000
Category	Ultrasonic proximity switch
Minimum order	1 Pcs
Document ID	EO-BAFA4BD31B
Generated	2026-08-05

Product Overview

Selected parameters SYSTEM Sensor HOUSING M12 SENSING RANGE up to 0,2 m CONNECTION M12 plug DC OUTPUT DC PNP MATERIAL Metal Others HOUSING M12 x 79 mm SENSING RANGE 0,2 m MATERIAL Stainless steel Ultrasound with direct detection, PNP output, NA/NC, Sensing distance 25 to 200 mm. Ultrasonic Sensor, Diffuse Reflective, M12 Stainless Steel housing, Plug M12 Connector, Sn 25-200mm, PNP Output, Supply Voltage 10-30VDC, Current Output 100mA, Operating Temperature -20-70C, Response Time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Conductive Level
--------------	--

Additional Product Information

Specifications

Rated operating distance25 mm ... 200 mmBlind zone25 mmDiameter12 mmAnalogue outputOtherOutput typePNPOutput functionConfigurableConnection typeM12 connectorHousing materialStainless steelRated power supply10 V ... 30 VDegree of protectionIP65

ETIM for UA12BLD02PPM1TR Sensors (EC001849)

Feature Name

Feature Value

Type of analogy output (EF003958)

Other

Type of electric connection (EF003961)

Connector M12

Type of switching output (EF003962)

PNP

Type of switch function (EF003963)

Programmable/configurable

Blind zone (EF003986)

25 mm

Width sensor (EF007094)

0 mm

Height of sensor (EF007283)

0 mm

Length of sensor (EF007334)

79 mm

Diameter sensor (EF007111)

12 mm

Adjustable distance (EF008209)

25 mm

Setting procedure (EF003994)

Teach-In

Measuring range length (EF008213)

25 mm

Explosion safety category for gas (EF003997)

None

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cylinder, screw-thread

Standard for interfaces (EF004017)

Other

No-load current (EF004028)

35 mA

Relative linearity deflection (EF004034)

1 %

Max. output current (EF001315)

100 mA

Ambient temperature (EF002386)

-20 °C

Supply voltage (EF004127)

10 V

Relative repeat accuracy (EF004100)

0.5 %

Switching frequency (EF003587)

20 Hz

Voltage type (EF000187)

DC

Synchronisation possible (EF004117)

No

Material active area of sensor (EF004133)

Glass

Housing material (EF001596)

Stainless steel

Material of cable sheath (EF004136)

Other

AWG-number (EF007010)

22

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / UA12BLD02PPM1TR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.