

INDUSTRIAL COMPONENT DATA

UA18EAD09NPM1TI CARLO GAVAZZI Selected parameters SYSTEM Sensor HOUSING M18 SENSING RANGE 0,2 to 1 m CONNECT..

Brand: CARLO GAVAZZI | Manufacturer Part Number: UA18EAD09NPM1TI



Manufacturer	CARLO GAVAZZI
MPN / Reference	UA18EAD09NPM1TI
Catalog number	10000
Category	Ultrasonic proximity switch
Minimum order	1 Pcs
Document ID	EO-260CC8E68C
Generated	2026-08-05

Product Overview

Selected parameters SYSTEM Sensor HOUSING M18 SENSING RANGE >0,2 to 1 m CONNECTION M12 plug DC OUTPUT 2 x NPN MATERIAL Metal Others HOUSING M18 x 91.7 mm SENSING RANGE 0,9 m MATERIAL Stainless steel

Ultrasound with direct detection, 2 x NPN digital output, Sensing distance 100 to 900 mm

Ultrasonic Sensor, Diffuse Reflective, M18 Stainless Steel INOX housing, M12 Connector, Sn 100-900mm, NPN Output x2, Supply Voltage 15-30VDC, Current Output 500mA, Operating Temperature -20-60C, Response Time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Conductive Level

Additional Product Information

Specifications

Rated operating distance100 mm ... 900 mmBlind zone100 mmDiameter18 mmAnalogue outputOtherOutput typeNPN/NPNOutput functionConfigurableConnection typeM12 connectorHousing materialStainless steelRated power supply15 V ... 30 VDegree of protectionIP67

ETIM for UA18EAD09NPM1TI Sensors (EC001849)

Feature Name

Feature Value

Type of analogy output (EF003958)

Other

Type of electric connection (EF003961)

Connector M12

Type of switching output (EF003962)

NPN/NPN

Type of switch function (EF003963)

Programmable/configurable

Blind zone (EF003986)

100 mm

Length of sensor (EF007334)

91.7 mm

Diameter sensor (EF007111)

18 mm

Adjustable distance (EF008209)

100 mm

Setting procedure (EF003994)

Teach-In

Measuring range length (EF008213)

100 mm

Construction type housing (EF004008)

Cylinder, screw-thread

Standard for interfaces (EF004017)

Other

No-load current (EF004028)

45 mA

Relative linearity deflection (EF004034)

1 %

Max. output current (EF001315)

100 mA

Ambient temperature (EF002386)

-20 °C

Supply voltage (EF004127)

15 V

Relative repeat accuracy (EF004100)

0.5 %

Switching frequency (EF003587)

4 Hz

Voltage type (EF000187)

DC

Synchronisation possible (EF004117)

No

Material active area of sensor (EF004133)

Glass

Housing material (EF001596)

Stainless steel

Material of cable sheath (EF004136)

Other

AWG-number (EF007010)

22

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / UA18EAD09NPM1TI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.