

INDUSTRIAL COMPONENT DATA

UA30EAD35PPTI CARLO GAVAZZI Selected parameters SYSTEM Sensor HOUSING M30 SENSING RANGE 3 m CONNECTION Cable..

Brand: CARLO GAVAZZI | Manufacturer Part Number: UA30EAD35PPTI



Manufacturer	CARLO GAVAZZI
MPN / Reference	UA30EAD35PPTI
Catalog number	10000
Category	Ultrasonic proximity switch
Minimum order	1 Pcs
Document ID	EO-0D3A09FF20
Generated	2026-08-04

Product Overview

Selected parameters SYSTEM Sensor HOUSING M30 SENSING RANGE >3 m CONNECTION Cable OUTPUT 2 x PNP MATERIAL Metal Others HOUSING M30 x 93 mm SENSING RANGE 3,5 m MATERIAL Stainless steel
Ultrasound with direct detection, digital output 2 x PNP, Sensing distance 350 to 3,500 mm
Ultrasonic Sensor, Diffuse Reflective, M30 Stainless Steel INOX housing, Cable Connector, Sn 350-3500mm, PNP Output x2, Supply 12-30VDC, Current Output 300mA, Operating Temperature -20-70C, Response Time < 250mS, Switching Frequency 2 Hz, IP67, Teach-in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Conductive Level

Additional Product Information

Specifications

Rated operating distance 350 mm ... 3500 mm Blind zone 350 mm Diameter 30 mm Analogue output Other Output type PNP/PNPOutput function Configurable Connection type Cable Housing material Stainless steel Rated power supply 12 V ... 30 V Degree of protection IP67

ETIM for UA30EAD35PPTI Sensors (EC001849)

Feature Name

Feature Value

Type of analogy output (EF003958)

Other

Type of electric connection (EF003961)

Cable

Type of switching output (EF003962)

PNP/PNP

Type of switch function (EF003963)

Programmable/configurable

Blind zone (EF003986)

350 mm

Length of sensor (EF007334)

93 mm

Diameter sensor (EF007111)

30 mm

Adjustable distance (EF008209)

350 mm

Setting procedure (EF003994)

Teach-In

Measuring range length (EF008213)

350 mm

Construction type housing (EF004008)

Cylinder, screw-thread

Standard for interfaces (EF004017)

Other

No-load current (EF004028)

50 mA

Relative linearity deflection (EF004034)

1 %

Max. output current (EF001315)

300 mA

Ambient temperature (EF002386)

-20 °C

Supply voltage (EF004127)

12 V

Relative repeat accuracy (EF004100)

1 %

Switching frequency (EF003587)

2 Hz

Voltage type (EF000187)

DC

Synchronisation possible (EF004117)

No

Material active area of sensor (EF004133)

Glass

Housing material (EF001596)

Stainless steel

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

AWG-number (EF007010)

22

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / UA30EAD35PPTI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.