

INDUSTRIAL COMPONENT DATA

UA30CAD35PPTI CARLO GAVAZZI Selected parameters SYSTEM Sensor HOUSING M30 SENSING RANGE 3 m CONNECTION Cable..

Brand: CARLO GAVAZZI | Manufacturer Part Number: UA30CAD35PPTI



Manufacturer	CARLO GAVAZZI
MPN / Reference	UA30CAD35PPTI
Catalog number	10000
Category	Ultrasonic proximity switch
Minimum order	1 Pcs
Document ID	EO-6DD65D95E7
Generated	2026-08-04

Product Overview

Selected parameters SYSTEM Sensor HOUSING M30 SENSING RANGE >3 m CONNECTION Cable OUTPUT 2 x PNP MATERIAL Plastic Others HOUSING M30 x 89.5 mm SENSING RANGE 3,5 m MATERIAL Thermoplastic polyester Ultrasound with direct detection, digital output 2 x PNP, Sensing distance 250 to 3500 mm. Ultrasonic Sensor, Diffuse Reflective, M18 PBT housing, Cable Connector, Sn 250-3500mm, PNP Output x2, Supply Voltage 12-30VDC, Current Output 100mA, Operating Temperature -20-70C, Response Time

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Conductive Level
--------------	--

Additional Product Information

Specifications

Rated operating distance250 mm ... 3500 mmBlind zone250 mmDiameter30 mmAnalogue outputOtherOutput typePNP/PNPOutput functionConfigurableConnection typeCableHousing materialPlasticRated power supply15 V ... 30 VDegree of protectionIP67

ETIM for UA30CAD35PPTI Sensors (EC001849)

Feature Name

Feature Value

Type of analogy output (EF003958)

Other

Type of electric connection (EF003961)

Cable

Type of switching output (EF003962)

PNP/PNP

Type of switch function (EF003963)

Programmable/configurable

Blind zone (EF003986)

250 mm

Length of sensor (EF007334)

89.8 mm

Diameter sensor (EF007111)

30 mm

Adjustable distance (EF008209)

250 mm

Setting procedure (EF003994)

Teach-In

Measuring range length (EF008213)

250 mm

Construction type housing (EF004008)

Cylinder, screw-thread

Standard for interfaces (EF004017)

Other

No-load current (EF004028)

50 mA

Relative linearity deflection (EF004034)

0.5 %

Max. output current (EF001315)

300 mA

Ambient temperature (EF002386)

-20 °C

Supply voltage (EF004127)

15 V

Relative repeat accuracy (EF004100)

0.2 %

Switching frequency (EF003587)

2 Hz

Voltage type (EF000187)

DC

Synchronisation possible (EF004117)

No

Material active area of sensor (EF004133)

Glass

Housing material (EF001596)

Plastic

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

AWG-number (EF007010)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / UA30CAD35PPTI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.