

INDUSTRIAL COMPONENT DATA

CLD2EB1BU24 CARLO GAVAZZI Selected parameters SYSTEM System HOUSING 1-DIN SENSING FUNCTION Filling or Emptyi..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CLD2EB1BU24



Manufacturer	CARLO GAVAZZI
MPN / Reference	CLD2EB1BU24
Catalog number	10000
Category	(Fill) level monitoring relay
Minimum order	1 Pcs
Document ID	EO-AAFBAC565C
Generated	2026-08-02

Product Overview

Selected parameters SYSTEM System HOUSING 1-DIN SENSING FUNCTION Filling or Emptying CONNECTION
Terminals OUTPUT Relay SPDT MATERIAL PA66 Others HOUSING 17.5 x 90 x 67.2 mm SENSING FUNCTION 250 oHm
to 500 koHm MATERIAL PA66

Conductive Level Controller

in 2 points, with potentiometer, Power supply: 24-240 VAC/DC

Conductive 2-point level controller, DIN rail mount, filing-emptying function, sensitivity 250 ohm -500 Kohm, 1 x SPDT relay
output, supply voltage 24-240VAC/DC, 17.5x90x67,2mm housing, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Conductive Level
--------------	--

Additional Product Information

Specifications

Number of input probes3Adjustable sensitivityNoMin on-delay time1 sMax on-delay time1 sMin off-delay time1 sMax
off-delay time1 sRated operating voltage20 V ... 265 VConnection typeScrew terminalsProduct width17.5 mm

ETIM for CLD2EB1BU24 Relays (EC001447)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection
With detachable clamps (EF003340)
No
Number of inputs for electrodes (EF003427)
3
Min. adjustable operate delay time (EF008195)
1 s
Max. permitted operate delay time (EF008194)
1 s
Min. adjustable off-delay time (EF008192)
1 s
Max. permitted off-delay time (EF008191)
1 s
Response value sensitivity adjustable (EF003429)
No
Number of contacts as normally closed contact (EF008255)
0
Number of contacts as normally open contact (EF008256)
0
Number of contacts as change-over contact (EF008257)
1
Physical measurement principle (EF008238)
Conductive
Cascadable (EF000507)
No
Width (EF000008)
17.5 mm
Height (EF000040)
90 mm
Depth (EF000049)
67.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / CLD2EB1BU24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.