

INDUSTRIAL COMPONENT DATA

CLD4MA2DM24 CARLO GAVAZZI Selected parameters SYSTEM System HOUSING 2-DIN SENSING FUNCTION Filling and Empty..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CLD4MA2DM24



Manufacturer	CARLO GAVAZZI
MPN / Reference	CLD4MA2DM24
Catalog number	10000
Category	(Fill) level monitoring relay
Minimum order	1 Pcs
Document ID	EO-AC5736CD85
Generated	2026-08-02

Product Overview

Selected parameters SYSTEM System HOUSING 2-DIN SENSING FUNCTION Filling and Emptying CONNECTION
Terminals OUTPUT Relay DPDT MATERIAL Plastic Others HOUSING 35,5 x 81 x 60 mm SENSING FUNCTION 250 oHm
to 500 koHm MATERIAL NORYL ADDITIONAL Alarm HiHi and LoLo
2 to 4 point conductive level controller with potentiometer, Power supply 24 VAC/DC
Conductive 2 to 4-point level controller, DIN rail mount, filling-emptying with multifunctions, sensitivity 250 ohm -500 Kohm,
SPST + SPDT relay output, supply voltage 24VAC/DC, 35.5x81x60,2mm housing, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Conductive Level

Additional Product Information

Specifications

Number of input probes5Adjustable sensitivityNoNumber of relay outputs1Min on-delay time1 sMax on-delay time1 sMin
off-delay time1 sMax off-delay time1 sRated operating voltage19.2 V ... 28.8 VConnection typeScrew terminalsProduct
width35.5 mm

ETIM for CLD4MA2DM24 Relays (EC001447)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection
With detachable clamps (EF003340)
No
Number of inputs for electrodes (EF003427)
5
Min. adjustable operate delay time (EF008195)
1 s
Max. permitted operate delay time (EF008194)
1 s
Min. adjustable off-delay time (EF008192)
1 s
Max. permitted off-delay time (EF008191)
1 s
Response value sensitivity adjustable (EF003429)
No
Number of contacts as normally closed contact (EF008255)
0
Number of contacts as normally open contact (EF008256)
1
Number of contacts as change-over contact (EF008257)
1
Physical measurement principle (EF008238)
Conductive
Cascadable (EF000507)
No
Width (EF000008)
35.5 mm
Height (EF000040)
81 mm
Depth (EF000049)
60.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / CLD4MA2DM24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.