

INDUSTRIAL COMPONENT DATA

CLD2EA1C230 CARLO GAVAZZI Selected parameters SYSTEM System HOUSING 2-DIN SENSING FUNCTION Filling or Emptyi..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CLD2EA1C230



Manufacturer	CARLO GAVAZZI
MPN / Reference	CLD2EA1C230
Catalog number	10000
Category	(Fill) level monitoring relay
Minimum order	1 Pcs
Document ID	EO-214AFF9615
Generated	2026-08-03

Product Overview

Selected parameters SYSTEM System HOUSING 2-DIN SENSING FUNCTION Filling or Emptying CONNECTION
Terminals OUTPUT Relay DPDT MATERIAL Plastic Others HOUSING 35,5 x 81 x 60 mm SENSING FUNCTION 250 ohm
to 500 kohm MATERIAL NORYL

2-point conductive level controller with potentiometer, Power supply 230 VAC

Conductive 2-point level controller, DIN rail mount, filling-emptying function, sensitivity 250 ohm -500 Kohm, 2 x DPDT relay
output, supply voltage 230VAC, 35.5x81x60,2mm housing, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Conductive Level

Additional Product Information

Specifications

Number of input probes3Adjustable sensitivityNoMin on-delay time1 sMax on-delay time1 sMin off-delay time1 sMax
off-delay time1 sRated operating voltage0 V ... 0 VConnection typeScrew terminalsProduct width35.5 mm

ETIM for CLD2EA1C230 Relays (EC001447)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

With detachable clamps (EF003340)

No

Number of inputs for electrodes (EF003427)

3

Min. adjustable operate delay time (EF008195)

1 s

Max. permitted operate delay time (EF008194)

1 s

Min. adjustable off-delay time (EF008192)

1 s

Max. permitted off-delay time (EF008191)

1 s

Response value sensitivity adjustable (EF003429)

No

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

0

Number of contacts as change-over contact (EF008257)

2

Physical measurement principle (EF008238)

Conductive

Cascadable (EF000507)

No

Width (EF000008)

35.5 mm

Height (EF000040)

81 mm

Depth (EF000049)

60.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / CLD2EA1C230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.